

FS48-750-C2-B Information



For Reference Only

Part Number FS48-750-C2-B
Manufacturer Triad Magnetics
Category Transformers
Power Transformers

Description XFRMR LAMINATED 36VA THRU HOLE

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FS48-750-C2-B Specifications

Manufacturer Part Number FS48-750-C2-B Manufacturer Triad Magnetics Category Transformers Package - Series Split Pack?, Class 2/3, FS Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 1.5A, Series 750mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 4200Vrms Weight 1.1 lbs (499g)		
Category Transformers Power Transformers Package Series Split Pack?, Class 2/3, FS Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 1.5A, Series 750mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation Weight Tinnugh Hole 1.1 lbs (499g)	Manufacturer Part Number	FS48-750-C2-B
Package Package Series Split Pack?, Class 2/3, FS Type Laminated Core Voltage - Primary Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 1.5A, Series 750mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation Veight 1.1 lbs (499g)	Manufacturer	Triad Magnetics
Package - Series Split Pack?, Class 2/3, FS Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 1.5A, Series 750mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 4200Vrms Weight	Category	Transformers
SeriesSplit Pack?, Class 2/3, FSTypeLaminated CoreVoltage - Primary115V, 230VVoltage - Secondary (Full Load)Parallel 24V, Series 48VCurrent - Output (Max)Parallel 1.5A, Series 750mAPrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4200VrmsWeight1.1 lbs (499g)		Power Transformers
Type Laminated Core Voltage - Primary 115V, 230V Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 1.5A, Series 750mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 4200Vrms Weight 1.1 lbs (499g)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 24V, Series 48V Current - Output (Max) Parallel 1.5A, Series 750mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Voltage - Isolation Voltage - Isolation 115V, 230V Parallel 24V, Series 48V Parallel 1.5A, Series 750mA Parallel 1.5A, Series 750mA Parallel 1.5A, Series 750mA Parallel 2.4V, Series 48V Paral	Series	Split Pack?, Class 2/3, FS
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 1.5A, Series 750mA Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Through Hole Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight Parallel 24V, Series 48V Parallel 1.5A, Series 750mA No 140 150 160 160 160 160 160 160 16	Туре	Laminated Core
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style Size / Dimension Fight - Seated (Max) Voltage - Isolation Weight Parallel 1.5A, Series 750mA Dual Pull Pull Pull Power P	Voltage - Primary	115V, 230V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 36 VA Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation 4200Vrms Weight No Dual No 1.1 lbs (499g)	Voltage - Secondary (Full Load)	Parallel 24V, Series 48V
Secondary Winding(s)DualCenter TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4200VrmsWeight1.1 lbs (499g)	Current - Output (Max)	Parallel 1.5A, Series 750mA
Center TapNoPower - Max36 VAMounting TypeThrough HoleTermination StylePC PinSize / Dimension66.68mm L x 55.55mm WHeight - Seated (Max)39.67mmVoltage - Isolation4200VrmsWeight1.1 lbs (499g)	Primary Winding(s)	Dual
Power - Max Mounting Type Through Hole Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) Voltage - Isolation 4200Vrms Weight 1.1 lbs (499g)	Secondary Winding(s)	Dual
Mounting Type Through Hole PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 4200Vrms Weight 1.1 lbs (499g)	Center Tap	No
Termination Style PC Pin Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 4200Vrms Weight 1.1 lbs (499g)	Power - Max	36 VA
Size / Dimension 66.68mm L x 55.55mm W Height - Seated (Max) 39.67mm Voltage - Isolation 4200Vrms Weight 1.1 lbs (499g)	Mounting Type	Through Hole
Height - Seated (Max) Voltage - Isolation Weight 39.67mm 4200Vrms 1.1 lbs (499g)	Termination Style	PC Pin
Voltage - Isolation 4200Vrms Weight 1.1 lbs (499g)	Size / Dimension	66.68mm L x 55.55mm W
Weight 1.1 lbs (499g)	Height - Seated (Max)	39.67mm
	Voltage - Isolation	4200Vrms
Report errors?	Weight	1.1 lbs (499g)
		Report errors?

FS48-750-C2-B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FS48-750-C2-B Payment Methods



















FS48-750-C2-B Shipping Methods













If you have any question about FS48-750-C2-B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com