

### **FSA150024A Information**



For Reference Only

Part Number FSA150024A
Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 24V 150W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **FSA150024A Specifications**

Manufacturer Part Number         FSA150024A           Manufacturer         Inventus Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         FSA 150           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         FSA 150           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Manufacturer Part Number	FSA150024A
Package         -           Series         FSA 150           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Manufacturer	Inventus Power
Package         -           Series         FSA 150           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         FSA 150           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Package	-
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Series	FSA 150
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         24V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.3A           Power (Watts)         150W (180W Forced Air)           Applications         ITE (Commercial)           Voltage - Isolation         -           Efficiency         91%           Operating Temperature         0°C ~ 70°C           Features         Universal Input           Mounting Type         Chassis Mount           Size / Dimension         5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Туре	Open Frame
Voltage - Output 124VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6.3APower (Watts)150W (180W Forced Air)ApplicationsITE (Commercial)Voltage - Isolation-Efficiency91%Operating Temperature0°C ~ 70°CFeaturesUniversal InputMounting TypeChassis MountSize / Dimension5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Fefficiency  Operating Temperature  O°C ~ 70°C  Features  Universal Input  Mounting Type  Size / Dimension  -  Current - Output (Max)  -  6.3A  150W (180W Forced Air)  ITE (Commercial)  Voltage - Isolation  -  Efficiency  91%  Over ~ 70°C  Universal Input  Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  Efficiency  Operating Temperature  O°C ~ 70°C  Features  Universal Input  Mounting Type  Size / Dimension  - Current - Output (Max)  6.3A  150W (180W Forced Air)  17E (Commercial)  - Commercial)  - Commercial  - Commerc	Voltage - Output 1	24V
Voltage - Output 4  Current - Output (Max)  6.3A  Power (Watts)  150W (180W Forced Air)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  91%  Operating Temperature  0°C ~ 70°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  -  Current - Output (Max)  6.3A  150W (180W Forced Air)  17E (Commercial)  -  Universal Input  Chassis Mount  5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Voltage - Output 2	-
Current - Output (Max)  6.3A  Power (Watts)  150W (180W Forced Air)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  91%  Operating Temperature  0°C ~ 70°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  6.3A  6.3A  150W (180W Forced Air)  -  Universal Input  Chassis Mount  5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  -  Efficiency  91%  Operating Temperature  0°C ~ 70°C  Features  Universal Input  Mounting Type  Chassis Mount  Size / Dimension  150W (180W Forced Air)  160W (180W Forced Air)  170W (180W Forced Air)	Voltage - Output 4	-
Applications ITE (Commercial)  Voltage - Isolation -  Efficiency 91%  Operating Temperature 0°C ~ 70°C  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Current - Output (Max)	6.3A
Voltage - Isolation  Efficiency 91%  Operating Temperature 0°C ~ 70°C  Features Universal Input  Mounting Type Chassis Mount  Size / Dimension 5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Power (Watts)	150W (180W Forced Air)
Efficiency 91%  Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Universal Input  Mounting Type Chassis Mount  Size / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.22^{\circ}\text{H } (127.0\text{mm x } 76.2\text{mm x } 30.9\text{mm})$	Applications	ITE (Commercial)
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$ FeaturesUniversal InputMounting TypeChassis MountSize / Dimension $5.00$ " L x $3.00$ " W x $1.22$ " H ( $127.0$ mm x $76.2$ mm x $30.9$ mm)	Voltage - Isolation	-
Features Universal Input  Mounting Type Chassis Mount  Size / Dimension  5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Efficiency	91%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Operating Temperature	0°C ~ 70°C
Size / Dimension 5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)	Features	Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.22" H (127.0mm x 76.2mm x 30.9mm)
		Report errors?

#### FSA150024A Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FSA150024A Payment Methods



















### FSA150024A Shipping Methods













If you have any question about FSA150024A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com