

FSOT1011E5K000KE

FSOT1011E5K000KE Information

Part Number FSOT1011E5K000KE

Manufacturer Vishay Huntington Electric Inc.

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 5K OHM 10% 10W

Package Radial, Flat Oval

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FSOT1011E5K000KE Specifications

Manufacturer Part NumberFSOT1011E5K000KEManufacturerVishay Huntington Electric Inc.CategoryResistorsPackageRadial, Flat OvalSeriesFSOTResistance5 kOhmsTolerance±10%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeSilicone CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.52mm)Height - Seated (Max)0.343" (8.71mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-		
CategoryResistorsPackageRadial, Flat OvalSeriesFSOTResistance5 kOhmsTolerance±10%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeSilicone CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.52mm)Height - Seated (Max)0.343" (8.71mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Manufacturer Part Number	FSOT1011E5K000KE
Chassis Mount Resistors Package Radial, Flat Oval Series FSOT Resistance 5 kOhms Tolerance ±10% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Manufacturer	Vishay Huntington Electric Inc.
PackageRadial, Flat OvalSeriesFSOTResistance5 kOhmsTolerance±10%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeSilicone CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.52mm)Height - Seated (Max)0.343" (8.71mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Category	Resistors
SeriesFSOTResistance5 kOhmsTolerance±10%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeSilicone CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.52mm)Height - Seated (Max)0.343" (8.71mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-		Chassis Mount Resistors
Resistance5 kOhmsTolerance±10%Power (Watts)10WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeSilicone CoatedMounting FeatureFlange Braces, Right AngleSize / Dimension0.750" L x 0.375" W (19.05mm x 9.52mm)Height - Seated (Max)0.343" (8.71mm)Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Package	Radial, Flat Oval
Tolerance ±10% Power (Watts) 10W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Series	FSOT
Power (Watts) Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Resistance	5 kOhms
Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Tolerance	±10%
Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Power (Watts)	10W
Operating Temperature Features Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Package / Case Radial, Flat Oval Failure Rate	Composition	Wirewound
Features - Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Temperature Coefficient	±260ppm/°C
Coating, Housing Type Silicone Coated Mounting Feature Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate Flange Braces, Right Angle 0.750" L x 0.375" W (19.05mm x 9.52mm) Solder Lugs Rodard Lugs Radial, Flat Oval	Features	-
Size / Dimension 0.750" L x 0.375" W (19.05mm x 9.52mm) Height - Seated (Max) 0.343" (8.71mm) Lead Style Solder Lugs Package / Case Radial, Flat Oval Failure Rate -	Coating, Housing Type	Silicone Coated
Height - Seated (Max) Lead Style Package / Case Radial, Flat Oval Failure Rate 0.343" (8.71mm) Solder Lugs Radial, Flat Oval	Mounting Feature	Flange Braces, Right Angle
Lead StyleSolder LugsPackage / CaseRadial, Flat OvalFailure Rate-	Size / Dimension	0.750" L x 0.375" W (19.05mm x 9.52mm)
Package / Case Radial, Flat Oval Failure Rate -	Height - Seated (Max)	0.343" (8.71mm)
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Flat Oval
Report errors?	Failure Rate	-
		Report errors?

FSOT1011E5K000KE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FSOT1011E5K000KE Payment Methods



















FSOT1011E5K000KE Shipping Methods













If you have any question about FSOT1011E5K000KE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com