

# FT600-2000-2

### FT600-2000-2 Information



For Reference Only

| Part Number  | FT600-2000-2   |  |
|--------------|--|--|
| Manufacturer | Littelfuse Inc.  |  |
| Category     | Circuit Protection<br>Electrical, Specialty Fuses  |  |
| Description  | FUSE BOARD MOUNT 2A 600VAC 2SMD  |  |
| Package      | 2-SMD, Square End Block  |  |
|              | For the pricing/inventory/lead time, please contact<br>us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com |  |



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# FT600-2000-2 Specifications

| Manufacturer Littelfuse Inc.   Category Circuit Protection   Electrical, Specialty Fuses Electrical, Specialty Fuses   Package 2-SMD, Square End Block   Series FT600, Raychem   Fuse Type Board Mount   Current Rating 2A   Voltage Rating - AC 600V   Voltage Rating - DC -   Response Time Fast   Applications Telecom   Features -   Class -   Approvals CSA, UL   Operating Temperature 55°C ~ 125°C   Breaking Capacity @ Rated Voltage 60A   Mounting Type Surface Mount |                                   |  |
|---|-----------------------------------|--|
| CategoryCircuit ProtectionElectrical, Specialty FusesPackage2-SMD, Square End BlockSeriesFT600, RaychemFuse TypeBoard MountCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsTelecomFeatures-Class-ApprovalsCSA, ULOperating Temperature60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm)   | Manufacturer Part Number          | FT600-2000-2   |
| ConstraintElectrical, Specialty FusesPackage2-SMD, Square End BlockSeriesFT600, RaychemFuse TypeBoard MountCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsTelecomFeatures-Class-ApprovalsCSA, ULOperating Temperature60ABreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)                                   | Manufacturer                      | Littelfuse Inc.  |
| Package2-SMD, Square End BlockSeriesFT600, RaychemFuse TypeBoard MountCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplications-Features-Class-ApprovalsCSA, ULOperating Type60ABreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm)  | Category                          | Circuit Protection   |
| Series FT600, Raychem   Fuse Type Board Mount   Current Rating 2A   Voltage Rating - AC 600V   Voltage Rating - DC -   Response Time Fast   Applications Telecom   Features -   Class -   Approvals CSA, UL   Operating Temperature 60A   Mounting Type 60A   Package / Case 2-SMD, Square End Block   Size / Dimension 0.402" L x 0.122" W x 0.122" W x 0.122" W x 0.120 mm x 3.10mm)  |                                   | Electrical, Specialty Fuses                                |
| Fuse TypeBoard MountCurrent Rating2AVoltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsTelecomFeatures-Class-ApprovalsCSA, ULOperating Temperature604Breaking Capacity @ Rated VoltageSurface MountPackage / Case-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm)   | Package                           | 2-SMD, Square End Block                                    |
| Current Rating 2A   Voltage Rating - AC 600V   Voltage Rating - DC -   Response Time Fast   Applications Telecom   Features -   Class -   Approvals CSA, UL   Operating Temperature 60A   Breaking Capacity @ Rated Voltage 60A   Mounting Type Surface Mount   Package / Case 2-SMD, Square End Block   Size / Dimension 0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)  | Series                            | FT600, Raychem   |
| Voltage Rating - AC600VVoltage Rating - DC-Response TimeFastApplicationsTelecomFeatures-Class-ApprovalsCSA, ULOperating Temperature60ABreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm)   | Fuse Type                         | Board Mount  |
| Voltage Rating - DC-Response TimeFastApplicationsTelecomFeatures-Class-Class-Operating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)  | Current Rating                    | 2A   |
| Response TimeFastApplicationsTelecomFeatures-Class-ApprovalsCSA, ULOperating Temperature60ABreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)  | Voltage Rating - AC               | 600V   |
| ApplicationsTelecomFeatures-Class-ApprovalsCSA, ULOperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Voltage Rating - DC               | -  |
| InInFeatures-Class-ApprovalsCSA, ULOperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)  | Response Time                     | Fast   |
| Class-ApprovalsCSA, ULOperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Applications                      | Telecom  |
| ApprovalsCSA, ULOperating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Features                          | -  |
| Operating Temperature-55°C ~ 125°CBreaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Class                             | -  |
| Breaking Capacity @ Rated Voltage60AMounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Approvals                         | CSA, UL  |
| Mounting TypeSurface MountPackage / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Operating Temperature             | -55°C ~ 125°C  |
| Package / Case2-SMD, Square End BlockSize / Dimension0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Breaking Capacity @ Rated Voltage | 60A  |
| Size / Dimension 0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm)   | Mounting Type                     | Surface Mount  |
|   | Package / Case                    | 2-SMD, Square End Block                                    |
| Report errors?  | Size / Dimension                  | 0.402" L x 0.122" W x 0.122" H (10.20mm x 3.10mm x 3.10mm) |
|   |                                   | Report errors?   |

#### FT600-2000-2 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# FT600-2000-2 Payment Methods



## FT600-2000-2 Shipping Methods



If you have any question about FT600-2000-2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com