



FVA100015A Information



For Reference Only

Part Number FVA100015A
Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 15V 100W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FVA100015A Specifications

Manufacturer Part Number FVA100015A Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series FVA100 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	•	
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series FVA100 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Manufacturer Part Number	FVA100015A
Package - Series FVA100 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Manufacturer	Inventus Power
Package - Series FVA100 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FVA100 Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Package	-
Number of Outputs 1 Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Series	FVA100
Voltage - Input 100 ~ 240 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Type	Open Frame
Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation - Efficiency Operating Temperature Pectures PFC, Universal Input Mounting Type Size / Dimension - Current - Output (Max) - Current - Output (Max) 6.7A 100W (120W Forced Air) ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature PFC, Universal Input Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Voltage - Input	100 ~ 240 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature O°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension - Carrent - Output (Max) - Commercial	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension - 100W (120W Forced Air) 100W (120W For	Voltage - Output 2	-
Current - Output (Max) 6.7A Power (Watts) 100W (120W Forced Air) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature O°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 100W (120W Forced Air) ITE (Commercial) - 88% Chassis Mount 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Voltage - Output 4	-
Applications ITE (Commercial) Voltage - Isolation - Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Current - Output (Max)	6.7A
Voltage - Isolation Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Power (Watts)	100W (120W Forced Air)
Efficiency 88% Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50 " L x 2.50 " W x 1.22 " H (114.0 mm x 63.5 mm x 30.9 mm)	Applications	ITE (Commercial)
Operating Temperature 0°C ~ 70°C Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Voltage - Isolation	-
Features PFC, Universal Input Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Efficiency	88%
Mounting Type Chassis Mount Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Operating Temperature	0°C ~ 70°C
Size / Dimension 4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)	Features	PFC, Universal Input
	Mounting Type	Chassis Mount
Donost organi	Size / Dimension	4.50" L x 2.50" W x 1.22" H (114.0mm x 63.5mm x 30.9mm)
Report errors		Report errors

FVA100015A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FVA100015A Payment Methods



















FVA100015A Shipping Methods













If you have any question about FVA100015A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com