



FVT02506E1R000JE Information

www.haleener.com

For Reference Only

Actual lengths will vary

Part Number FVT02506E1R000JE

Manufacturer Vishay Huntington Electric Inc.

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 1 OHM 5% 25W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FVT02506E1R000JE Specifications

Manufacturer Part Number Manufacturer Vishay Huntington Electric Inc. Category Resistors Chassis Mount Resistors Package Radial, Tubular FVT Resistance 1 Ohms Tolerance ±5% Power (Watts) Composition Wirewound Temperature Coefficient 4400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Mounting Feature Brackets (not included) Size / Dimension Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate Vishay Huntington Electric Inc. Resistance Radial, Tubular Fialure Rate		
CategoryResistorsPackageRadial, TubularSeriesFVTResistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	FVT02506E1R000JE
Chassis Mount Resistors Package Radial, Tubular Series FVT Resistance 1 Ohms Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Manufacturer	Vishay Huntington Electric Inc.
PackageRadial, TubularSeriesFVTResistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesFVTResistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance1 OhmsTolerance±5%Power (Watts)25WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 25W Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Series	FVT
Power (Watts) Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Resistance	1 Ohms
Composition Wirewound Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Tolerance	±5%
Temperature Coefficient ±400ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Power (Watts)	25W
Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate - Solver Lugs	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Temperature Coefficient	±400ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets (not included) Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	-
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
	Failure Rate	-
Report errors?		Report errors?

FVT02506E1R000JE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FVT02506E1R000JE Payment Methods



















FVT02506E1R000JE Shipping Methods













If you have any question about FVT02506E1R000JE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com