



### FVT10006E1R000JE Information

www.helsener.com

For Reference Only

Actual lengths will vary

Part Number FVT10006E1R000JE

Manufacturer Vishay Huntington Electric Inc.

**Category** Resistors

**Chassis Mount Resistors** 

**Description** RES CHAS MNT 1 OHM 5% 100W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# FVT10006E1R000JE Specifications

Manufacturer Part NumberFVT10006E1R000JEManufacturerVishay Huntington Electric Inc.CategoryResistorsPackageRadial, TubularSeriesFVTResistance1 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.750" Dia x 6.500" L (19.05mm x 165.10mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeriesFVTResistance1 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.750" Dia x 6.500" L (19.05mm x 165.10mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	FVT10006E1R000JE
Chassis Mount Resistors  Package Radial, Tubular  Series FVT  Resistance 1 Ohms  Tolerance ±5%  Power (Watts) 100W  Composition Wirewound  Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 350°C  Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Manufacturer	Vishay Huntington Electric Inc.
PackageRadial, TubularSeriesFVTResistance1 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.750" Dia x 6.500" L (19.05mm x 165.10mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesFVTResistance1 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.750" Dia x 6.500" L (19.05mm x 165.10mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance1 OhmsTolerance±5%Power (Watts)100WCompositionWirewoundTemperature Coefficient±400ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.750" Dia x 6.500" L (19.05mm x 165.10mm)Height - Seated (Max)-Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5%  Power (Watts) 100W  Composition Wirewound  Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Series	FVT
Power (Watts)  Composition  Wirewound  ±400ppm/°C  Operating Temperature  -55°C ~ 350°C  Features  - Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  Size / Dimension  0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -  100W  Wirewound  ### ### ### #### ###################	Resistance	1 Ohms
Composition Wirewound  Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 350°C  Features -  Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Tolerance	±5%
Temperature Coefficient ±400ppm/°C  Operating Temperature -55°C ~ 350°C  Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate	Power (Watts)	100W
Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated  Mounting Feature Brackets (not included)  Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max) - Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate	Temperature Coefficient	±400ppm/°C
Coating, Housing Type  Vitreous Enamel Coated  Mounting Feature  Brackets (not included)  0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max)  -  Lead Style  Package / Case  Radial, Tubular  Failure Rate  Vitreous Enamel Coated  Brackets (not included)  0.750" Dia x 6.500" L (19.05mm x 165.10mm)  -  Lead Style  Solder Lugs  Radial, Tubular	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets (not included) Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm) Height - Seated (Max) - Lead Style Solder Lugs Package / Case Radial, Tubular Failure Rate -	Features	-
Size / Dimension 0.750" Dia x 6.500" L (19.05mm x 165.10mm)  Height - Seated (Max) -  Lead Style Solder Lugs  Package / Case Radial, Tubular  Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max)  Lead Style  Package / Case  Radial, Tubular  Failure Rate  -	Mounting Feature	Brackets (not included)
Lead StyleSolder LugsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.750" Dia x 6.500" L (19.05mm x 165.10mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Solder Lugs
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

#### FVT10006E1R000JE Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### FVT10006E1R000JE Payment Methods



















## FVT10006E1R000JE Shipping Methods













If you have any question about FVT10006E1R000JE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com