

FVWL20A1E2K000JE

FVWL20A1E2K000JE Information



For Reference Only

Part Number FVWL20A1E2K000JE

Manufacturer Vishay Huntington Electric Inc.

Category Resistors

Chassis Mount Resistors

Description RES CHAS MNT 2K OHM 5% 20W

Package Radial, Tubular

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FVWL20A1E2K000JE Specifications

Manufacturer Part NumberFVWL20A1E2K000JEManufacturerVishay Huntington Electric Inc.CategoryResistorsPackageRadial, TubularSeriesFVWLResistance2 kOhmsTolerance±5%Power (Watts)20WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.437" Dia x 2.000" L (11.11mm x 50.80mm)Height - Seated (Max)-Lead StyleCombo LeadsPackage / CaseRadial, TubularFailure Rate-Report errors?		
CategoryResistorsPackageRadial, TubularSeriesFVWLResistance2 kOhmsTolerance±5%Power (Watts)20WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.437" Dia x 2.000" L (11.11mm x 50.80mm)Height - Seated (Max)-Lead StyleCombo LeadsPackage / CaseRadial, TubularFailure Rate-	Manufacturer Part Number	FVWL20A1E2K000JE
Chassis Mount Resistors Package Radial, Tubular Series FVWL Resistance 2 kOhms Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate	Manufacturer	Vishay Huntington Electric Inc.
PackageRadial, TubularSeriesFVWLResistance2 kOhmsTolerance±5%Power (Watts)20WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.437" Dia x 2.000" L (11.11mm x 50.80mm)Height - Seated (Max)-Lead StyleCombo LeadsPackage / CaseRadial, TubularFailure Rate-	Category	Resistors
SeriesFVWLResistance2 kOhmsTolerance±5%Power (Watts)20WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.437" Dia x 2.000" L (11.11mm x 50.80mm)Height - Seated (Max)-Lead StyleCombo LeadsPackage / CaseRadial, TubularFailure Rate-		Chassis Mount Resistors
Resistance2 kOhmsTolerance±5%Power (Watts)20WCompositionWirewoundTemperature Coefficient±260ppm/°COperating Temperature-55°C ~ 350°CFeatures-Coating, Housing TypeVitreous Enamel CoatedMounting FeatureBrackets (not included)Size / Dimension0.437" Dia x 2.000" L (11.11mm x 50.80mm)Height - Seated (Max)-Lead StyleCombo LeadsPackage / CaseRadial, TubularFailure Rate-	Package	Radial, Tubular
Tolerance ±5% Power (Watts) 20W Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Series	FVWL
Power (Watts) Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Resistance	2 kOhms
Composition Wirewound Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Tolerance	±5%
Temperature Coefficient ±260ppm/°C Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Power (Watts)	20W
Operating Temperature -55°C ~ 350°C Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate - Sonother Associated Failure Rate	Composition	Wirewound
Features - Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate	Temperature Coefficient	±260ppm/°C
Coating, Housing Type Vitreous Enamel Coated Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Operating Temperature	-55°C ~ 350°C
Mounting Feature Brackets (not included) Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Features	-
Size / Dimension 0.437" Dia x 2.000" L (11.11mm x 50.80mm) Height - Seated (Max) - Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Coating, Housing Type	Vitreous Enamel Coated
Height - Seated (Max) Lead Style Combo Leads Package / Case Radial, Tubular Failure Rate -	Mounting Feature	Brackets (not included)
Lead StyleCombo LeadsPackage / CaseRadial, TubularFailure Rate-	Size / Dimension	0.437" Dia x 2.000" L (11.11mm x 50.80mm)
Package / Case Radial, Tubular Failure Rate -	Height - Seated (Max)	-
Failure Rate -	Lead Style	Combo Leads
	Package / Case	Radial, Tubular
Report errors?	Failure Rate	-
		Report errors?

FVWL20A1E2K000JE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FVWL20A1E2K000JE Payment Methods



















FVWL20A1E2K000JE Shipping Methods













If you have any question about FVWL20A1E2K000JE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com