

FW5012-760-NC Information

For Reference Only

Part Number FW5012-760-NC **Manufacturer** Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 50W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FW5012-760-NC Specifications

Manufacturer Part Number FW5012-760-NC Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer Part Number	FW5012-760-NC
Package - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer	Inventus Power
Package - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) $4.15A$ Power (Watts) $50W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorBarrel Plug, $2.5 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension 5.00° L x 3.00° W x 1.30° H ($127.0 \text{mm x } 76.2 \text{mm x } 33.0 \text{mm}$)	Series	FW50
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Region Utilized	International
Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00°L x 3.00° W x 1.30° H (127.0mm x 76.2mm x 33.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 4.15A Power (Watts) No Load Power Consumption Polarization Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 12V 4.15A 4.15A Power (Watts) FOW OW OW OW OW OW OW Size / Dimension 12V OW Automatic Max Automatic M	Input Type	Cord (Sold Separately)
Current - Output (Max) 4.15A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) $50W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature 0° C ~ 60° COutput ConnectorBarrel Plug, 2.5 mm I.D. $x 5.5$ mm O.D. $x 9.5$ mmSize / Dimension 5.00 " L $x 3.00$ " W $x 1.30$ " H (127.0 mm $x 76.2$ mm $x 33.0$ mm)	Voltage - Output	12V
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature 0° C ~ 60° COutput ConnectorBarrel Plug, $2.5 \text{mm I.D. x } 5.5 \text{mm O.D. x } 9.5 \text{mm}$ Size / Dimension 5.00 " L x 3.00 " W x 1.30 " H ($127.0 \text{mm x } 76.2 \text{mm x } 33.0 \text{mm}$)	Current - Output (Max)	4.15A
PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension 5.00 " L $x 3.00$ " W $x 1.30$ " H (127.0mm $x 76.2\text{mm}$ $x 33.0\text{mm}$)	Power (Watts)	50W
Applications ITE (Commercial) Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.00^{\circ}\text{L x } 3.00^{\circ}\text{W x } 1.30^{\circ}\text{H } (127.0\text{mm x } 76.2\text{mm x } 33.0\text{mm})$	No Load Power Consumption	-
Efficiency 80% Operating Temperature 0°C ~ 60 °C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.00^{\circ}\text{L x }3.00^{\circ}\text{W x }1.30^{\circ}\text{H }(127.0\text{mm x }76.2\text{mm x }33.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Efficiency	80%
Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)
		Report errors?

FW5012-760-NC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FW5012-760-NC Payment Methods



















FW5012-760-NC Shipping Methods













If you have any question about FW5012-760-NC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com