

FW5024-760-NC Information

r.com

For Reference Only

Part Number FW5024-760-NC **Manufacturer** Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 50W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FW5024-760-NC Specifications

Manufacturer Part Number FW5024-760-NC Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)			
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer Part Number	FW5024-760-NC	
Package - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Manufacturer	Inventus Power	
Package - Series FW50 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)	
SeriesFW50Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $24V$ Current - Output (Max) $2.1A$ Power (Watts) $50W$ No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorBarrel Plug, $2.5 \text{ mm I.D. x } 5.5 \text{ mm O.D. x } 9.5 \text{ mm}$ Size / Dimension 5.00° L x 3.00° W x 1.30° H (127.0mm x $76.2 \text{ mm x } 33.0 \text{ mm}$)		AC DC Desktop, Wall Adapters	
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Package	-	
Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Series	FW50	
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 24V Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Region Utilized	International	
Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00°L x 3.00° W x 1.30° H (127.0mm x 76.2mm x 33.0mm)	Form	Desktop (Class I)	
Voltage - Output Current - Output (Max) 2.1A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 24V 24V 24V 2.1A Power (Watts) FOW OW OW OW OW OW OW Size / Dimension Dow OW OW OW OW OW OW OW OW OW O	Input Type	Cord (Sold Separately)	
Current - Output (Max) 2.1A Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Input	100 ~ 240 VAC	
Power (Watts) 50W No Load Power Consumption - Polarization Positive Center Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Voltage - Output	24V	
No Load Power Consumption-PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension 5.00 " L $x 3.00$ " W $x 1.30$ " H (127.0mm x 76.2mm x 33.0mm)	Current - Output (Max)	2.1A	
PolarizationPositive CenterApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00 " L x 3.00 " W x 1.30 " H (127.0mm x 76.2mm x 33.0mm)	Power (Watts)	50W	
Applications ITE (Commercial) Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.00^{\circ}\text{L} \times 3.00^{\circ}\text{W} \times 1.30^{\circ}\text{H} (127.0\text{mm} \times 76.2\text{mm} \times 33.0\text{mm})$	No Load Power Consumption	-	
Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00 " L x 3.00 " W x 1.30 " H (127.0mm x 76.2 mm x 33.0 mm)	Polarization	Positive Center	
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.00^{\circ}\text{L} \times 3.00^{\circ}\text{W} \times 1.30^{\circ}\text{H} (127.0\text{mm} \times 76.2\text{mm} \times 33.0\text{mm})$	Applications	ITE (Commercial)	
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Efficiency	80%	
Size / Dimension 5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	Operating Temperature	0°C ~ 60°C	
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm	
Report errors?	Size / Dimension	5.00" L x 3.00" W x 1.30" H (127.0mm x 76.2mm x 33.0mm)	
			Report errors?

FW5024-760-NC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FW5024-760-NC Payment Methods



















FW5024-760-NC Shipping Methods













If you have any question about FW5024-760-NC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com