



FW7212-D5-NC Information

Part Number FW7212-D5-NC **Manufacturer** Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 72W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FW7212-D5-NC Specifications

Manufacturer Part Number FW7212-D5-NC Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series FW72 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FW72 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Manufacturer Part Number	FW7212-D5-NC
Package - Series FW72 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Manufacturer	Inventus Power
Package - Series FW72 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FW72 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output $12V$ Current - Output (Max) $6A$ Power (Watts) $72W$ No Load Power Consumption-Polarization-ApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorDIN, 5 PinSize / Dimension 6.50° L x 3.85° W x 2.60° H (165.0 mm x 98.0 mm x 66.0 mm)	Series	FW72
Input Type Cord (Sold Separately) Voltage - Input 100 ~ 240 VAC Voltage - Output 12V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Region Utilized	International
Voltage - Input $100 \sim 240 \text{ VAC}$ Voltage - Output 12 V Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption-Polarization-ApplicationsITE (Commercial)Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorDIN, 5 PinSize / Dimension $6.50^{\circ}\text{L x } 3.85^{\circ}\text{W x } 2.60^{\circ}\text{H } (165.0 \text{mm x } 98.0 \text{mm x } 66.0 \text{mm})$	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 12V 6A TOW TOW TOW TOW TOW TOW TOW TO	Input Type	Cord (Sold Separately)
Current - Output (Max) 6A Power (Watts) 72W No Load Power Consumption - Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Voltage - Input	100 ~ 240 VAC
Power (Watts) $72W$ No Load Power Consumption-Polarization-ApplicationsITE (Commercial)Efficiency 80% Operating Temperature 0° C ~ 60° COutput ConnectorDIN, 5 PinSize / Dimension 6.50 " L x 3.85 " W x 2.60 " H (165.0 mm x 98.0 mm x 66.0 mm)	Voltage - Output	12V
No Load Power Consumption-Polarization-ApplicationsITE (Commercial)Efficiency 80% Operating Temperature 0° C ~ 60° COutput ConnectorDIN, 5 PinSize / Dimension 6.50 " L x 3.85 " W x 2.60 " H (165.0 mm x 98.0 mm x 66.0 mm)	Current - Output (Max)	6A
Polarization - Applications ITE (Commercial) Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 5 Pin Size / Dimension $6.50^{\circ}\text{L x } 3.85^{\circ}\text{W x } 2.60^{\circ}\text{H } (165.0\text{mm x } 98.0\text{mm x } 66.0\text{mm})$	Power (Watts)	72W
Applications ITE (Commercial) Efficiency 80% Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 5 Pin Size / Dimension $6.50^{\circ}\text{L x } 3.85^{\circ}\text{W x } 2.60^{\circ}\text{H } (165.0 \text{mm x } 98.0 \text{mm x } 66.0 \text{mm})$	No Load Power Consumption	-
Efficiency 80% Operating Temperature 0°C ~ 60 °C Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 5 Pin Size / Dimension $6.50^{\circ}\text{L x } 3.85^{\circ}\text{W x } 2.60^{\circ}\text{H } (165.0\text{mm x } 98.0\text{mm x } 66.0\text{mm})$	Applications	ITE (Commercial)
Output Connector DIN, 5 Pin Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Efficiency	80%
Size / Dimension 6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	DIN, 5 Pin
Report errors?	Size / Dimension	6.50" L x 3.85" W x 2.60" H (165.0mm x 98.0mm x 66.0mm)
		Report errors?

FW7212-D5-NC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FW7212-D5-NC Payment Methods



















FW7212-D5-NC Shipping Methods













If you have any question about FW7212-D5-NC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com