

FWA-300B(10) Information

Heisener.com

Part Number FWA-300B(10)

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE 150V 300A SEMI-COND **Package** Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA-300B(10) Specifications

Manufacturer Part NumberFWA-300B(10)ManufacturerEatonCategoryCircuit ProtectionBekageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Manufacturer Part Number	FWA-300B(10)
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWA Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - C Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Category	Circuit Protection
SeriesFWAFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating300AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension	Series	FWA
Voltage Rating - AC Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 150V 15	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Current Rating	300A
Response Time - Applications - Electrical, Industrial - Class - Class - Approvals - CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case - Cylindrical, Blade Terminal (Bolt) Size / Dimension - 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Voltage Rating - AC	150V
Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Voltage Rating - DC	150V
Features - Class - Class - CE, UR Approvals CE, UR Operating Temperature - Facking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Response Time	-
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Approvals	CE, UR
Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Breaking Capacity @ Rated Voltage	100kA AC, 20kA DC
Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 1.156" L (25.40mm x 29.36mm)
		Report errors?

FWA-300B(10) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA-300B(10) Payment Methods





















FWA-300B(10) Shipping Methods













If you have any question about FWA-300B(10), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com