

FWA-350B Information

www lisener.com

Part Number FWA-350B Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionSEMI-COND FUSE 350A 150V AC**Package**Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA-350B Specifications

Manufacturer Part NumberFWA-350BManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Manufacturer Part Number	FWA-350B
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWA Fuse Type Cartridge Current Rating 350A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Industrial Features - CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Solt Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Category	Circuit Protection
SeriesFWAFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating350AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage100kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension	Series	FWA
Voltage Rating - AC Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 150V 150V 150V 160V 16	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Current Rating	350A
Response Time - Applications - Electrical, Industrial - Class - Class - Approvals - CE, UR - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type - Bolt - Package / Case - Cylindrical, Blade Terminal (Bolt) - Size / Dimension - 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Voltage Rating - AC	150V
Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Voltage Rating - DC	150V
Features - Class - Class - CE, UR Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Response Time	-
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Class	-
Breaking Capacity @ Rated Voltage 100kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Approvals	CE, UR
Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Breaking Capacity @ Rated Voltage	100kA AC, 20kA DC
Size / Dimension 1.000" Dia x 1.156" L (25.40mm x 29.36mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.000" Dia x 1.156" L (25.40mm x 29.36mm)
		Report errors?

FWA-350B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA-350B Payment Methods



















FWA-350B Shipping Methods













If you have any question about FWA-350B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com