

FWA-500ASI4 Information

Heisener.com

Part Number FWA-500ASI4

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionBUSS SEMICONDUCTOR FUSEPackageCylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA-500ASI4 Specifications

Manufacturer Part NumberFWA-500ASI4ManufacturerEatonCategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.250" L (38.10mm x 31.75mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Manufacturer Part Number	FWA-500ASI4
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWA Fuse Type Cartridge Current Rating 500A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time - Applications Electrical, Industrial Features Indicating Class - Indicating Class - CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage AC 200kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWAFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Category	Circuit Protection
SeriesFWAFuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.250" L (38.10mm x 31.75mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating500AVoltage Rating - AC150VVoltage Rating - DC150VResponse Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 20kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 500A Voltage Rating - AC 150V Voltage Rating - DC 150V Response Time - Capacity @ Rated Voltage Industrial Capacity @ Rated Voltage Capacity @ Rated Volt	Series	FWA
Voltage Rating - AC Voltage Rating - DC 150V Response Time Applications Electrical, Industrial Indicating Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 150V 150V 160V 160V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Current Rating	500A
Response Time - Applications - Electrical, Industrial Features - Indicating Class - Approvals - CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case - Cylindrical, Blade Terminal (Bolt) Size / Dimension - 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Voltage Rating - AC	150V
Applications Electrical, Industrial Features Indicating Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Voltage Rating - DC	150V
Features Indicating Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Response Time	-
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 20kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Approvals	CE, UR
Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Breaking Capacity @ Rated Voltage	200kA AC, 20kA DC
Size / Dimension 1.500" Dia x 1.250" L (38.10mm x 31.75mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 1.250" L (38.10mm x 31.75mm)
		Report errors?

FWA-500ASI4 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA-500ASI4 Payment Methods



















FWA-500ASI4 Shipping Methods













If you have any question about FWA-500ASI4, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com