



FWA120024A-12A Information

Part Number FWA120024A-12A Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA120024A-12A Specifications

Manufacturer Part Number FWA120024A-12A Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWA120 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWA120 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Manufacturer Part Number	FWA120024A-12A
Package - Series FWA120 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Manufacturer	Inventus Power
Package - Series FWA120 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FWA120 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class I)Input TypeCord (Sold Separately)Voltage - Input85 ~ 264 VACVoltage - Output24VCurrent - Output (Max)5APower (Watts)120WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorDIN, 8 PinSize / Dimension7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Package	-
FormDesktop (Class I)Input Type $Cord (Sold Separately)$ Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorDIN, 8 PinSize / Dimension $7.56^{\circ}\text{L} \times 2.45^{\circ}\text{W} \times 1.52^{\circ}\text{H} (192.0\text{mm} \times 62.2\text{mm} \times 38.7\text{mm})$	Series	FWA120
Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Region Utilized	International
Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 85 ~ 264 VAC 24V Current - Output (Max) 5A 120W Commercial 500mW (Max) - Commercial 120W 120W	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 5A Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 24V 5A Current - Output (Max) 5A 120W 120W	Input Type	Cord (Sold Separately)
Current - Output (Max) Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 5A 120W	Voltage - Input	85 ~ 264 VAC
Power (Watts) 120W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 120W 500mW (Max) - Commercial 120W 120mm x 62.2mm x 38.7mm)	Voltage - Output	24V
No Load Power Consumption 500mW (Max) Polarization - ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Current - Output (Max)	5A
Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Power (Watts)	120W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Polarization	-
Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Applications	ITE (Commercial)
Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Efficiency	Level V
Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	DIN, 8 Pin
	Size / Dimension	7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)
Report errors?		Report errors?

FWA120024A-12A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA120024A-12A Payment Methods



















FWA120024A-12A Shipping Methods













If you have any question about FWA120024A-12A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com