



FWA150018A-12B Information



For Reference Only

Part Number FWA150018A-12B **Manufacturer** Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 18V 150W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA150018A-12B Specifications

Manufacturer Part Number FWA150018A-12B Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series FWA150 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWA150 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Manufacturer Part Number	FWA150018A-12B
Package - Series FWA150 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Manufacturer	Inventus Power
Package - Series FWA150 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FWA150 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Series	FWA150
Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Region Utilized	North America
Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Input Type	Cord
Current - Output (Max) 8.3A Power (Watts) 149W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Voltage - Input	85 ~ 264 VAC
Power (Watts) $149W$ No Load Power Consumption $500mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorDIN, 8 PinSize / Dimension 7.56 " L x 2.45 " W x 1.52 " H (192.0mm x 62.2 mm x 38.7 mm)	Voltage - Output	18V
No Load Power Consumption 500mW (Max) Polarization - ITE (Commercial) Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Current - Output (Max)	8.3A
Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Power (Watts)	149W
Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension $7.56^{\circ}\text{L} \times 2.45^{\circ}\text{W} \times 1.52^{\circ}\text{H} (192.0 \text{mm} \times 62.2 \text{mm} \times 38.7 \text{mm})$	Applications	ITE (Commercial)
Output Connector DIN, 8 Pin Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Efficiency	Level V
Size / Dimension 7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	DIN, 8 Pin
Report errors?	Size / Dimension	7.56" L x 2.45" W x 1.52" H (192.0mm x 62.2mm x 38.7mm)
		Report errors?

FWA150018A-12B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA150018A-12B Payment Methods





















FWA150018A-12B Shipping Methods













If you have any question about FWA150018A-12B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com