



FWA180018A-13B Information



For Reference Only

Part Number FWA180018A-13B Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 18V 180W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA180018A-13B Specifications

Manufacturer Part Number FWA180018A-13B Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series FWA180 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWA180 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Manufacturer Part Number	FWA180018A-13B
Package - Series FWA180 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Manufacturer	Inventus Power
Package - Series FWA180 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FWA180 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output18VCurrent - Output (Max)10APower (Watts)180WNo Load Power Consumption500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorRectangular, 6 PositionSize / Dimension8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Series	FWA180
Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorRectangular, 6 PositionSize / Dimension $8.20^{\circ}\text{L} \times 2.90^{\circ}\text{ W} \times 1.60^{\circ}\text{ H} (208.0\text{mm} \times 73.0\text{mm} \times 39.0\text{mm})$	Region Utilized	North America
Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 10A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 10A Power (Watts) No Load Power Consumption Polarization Applications ITE (Commercial) Efficiency Level V Operating Temperature O°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 18V 10A 18W 18W 18W 18W 18W 18W 18W 18	Input Type	Cord
Current - Output (Max) Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 10A 180W 180	Voltage - Input	85 ~ 264 VAC
Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 180W Size / Dimension	Voltage - Output	18V
No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Current - Output (Max)	10A
Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Power (Watts)	180W
Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C $\sim 60^{\circ}$ C Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorRectangular, 6 PositionSize / Dimension $8.20^{\circ}\text{L x } 2.90^{\circ}\text{W x } 1.60^{\circ}\text{H } (208.0\text{mm x } 73.0\text{mm x } 39.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Rectangular, 6 Position Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Efficiency	Level V
Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Rectangular, 6 Position
Report errors?	Size / Dimension	8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)
		Report errors?

FWA180018A-13B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA180018A-13B Payment Methods



















FWA180018A-13B Shipping Methods













If you have any question about FWA180018A-13B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com