



FWA180048A-11A Information

Part Number FWA180048A-11A Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA180048A-11A Specifications

Manufacturer Part Number FWA180048A-11A Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) Reckage - Series FWA180 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWA180 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Manufacturer Part Number	FWA180048A-11A
Package - Series FWA180 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Manufacturer	Inventus Power
Package - Series FWA180 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FWA180 Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)		AC DC Desktop, Wall Adapters
Region Utilized International Form Desktop (Class I) Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Package	-
FormDesktop (Class I)Input Type $Cord$ (Sold Separately)Voltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output $48V$ Current - Output (Max) $3.75A$ Power (Watts) $180W$ No Load Power Consumption $500mW$ (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 60^{\circ}C$ Output ConnectorDIN, 5 PinSize / Dimension $8.20^{\circ}L \times 2.90^{\circ}W \times 1.60^{\circ}H$ ($208.0mm \times 73.0mm \times 39.0mm$)	Series	FWA180
Input Type Cord (Sold Separately) Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Region Utilized	International
Voltage - Input 85 ~ 264 VAC Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Form	Desktop (Class I)
Voltage - Output 48V Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 3.75A Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 3.75A 180W Comwercial 500mW (Max) - Commercial 175 (Commercial) 176 (Commercial) 177 (Commercial) 178 (Commercial) 179 (Commercial) 170 (Commercial) 170 (Commercial) 170 (Commercial) 171 (Commercial) 172 (Commercial) 173 (Commercial) 174 (Commercial) 175 (Commercial) 176 (Commercial) 177 (Commercial) 178 (Commercial) 179 (Commercial) 170 (Commercial) 171 (Commercial) 171 (Commercial) 172 (Commercial) 173 (Commercial) 174 (Commercial) 175 (Commercial) 176 (Commercial) 177 (Commercial) 177 (Commercial) 178 (Commercial) 179 (Commercial) 170	Voltage - Input	85 ~ 264 VAC
Power (Watts) 180W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Voltage - Output	48V
No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Current - Output (Max)	3.75A
Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 5 Pin Size / Dimension $8.20^{\circ}\text{L} \times 2.90^{\circ}\text{W} \times 1.60^{\circ}\text{H} (208.0 \text{mm} \times 73.0 \text{mm} \times 39.0 \text{mm})$	Power (Watts)	180W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 5 Pin Size / Dimension $8.20^{\circ}\text{L x } 2.90^{\circ}\text{W x } 1.60^{\circ}\text{H } (208.0\text{mm x } 73.0\text{mm x } 39.0\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorDIN, 5 PinSize / Dimension $8.20^{\circ}\text{L x } 2.90^{\circ}\text{W x } 1.60^{\circ}\text{H } (208.0\text{mm x } 73.0\text{mm x } 39.0\text{mm})$	Applications	ITE (Commercial)
Output Connector DIN, 5 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Efficiency	Level V
Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	DIN, 5 Pin
Report errors?	Size / Dimension	8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)
		Report errors?

FWA180048A-11A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA180048A-11A Payment Methods



















FWA180048A-11A Shipping Methods













If you have any question about FWA180048A-11A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com