



FWA220024A-12B Information



For Reference Only

Part Number FWA220024A-12B Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 220W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWA220024A-12B Specifications

Manufacturer Part Number FWA220024A-12B Manufacturer Inventus Power Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWA220 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWA220 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Manufacturer Part Number	FWA220024A-12B
Package - Series FWA220 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Manufacturer	Inventus Power
Package - Series FWA220 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series FWA220 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Package	-
FormDesktop (Class I)Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max)Polarization-ApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorDIN, 8 PinSize / Dimension $8.20^{\circ}\text{L} \times 2.90^{\circ}\text{W} \times 1.60^{\circ}\text{H} (208.0\text{mm} \times 73.0\text{mm} \times 39.0\text{mm})$	Series	FWA220
Input Type Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) Power (Watts) No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Region Utilized	North America
Voltage - Input 85 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 9.2A Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 9.2A Power (Watts) No Load Power Consumption Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 24V 9.2A 9.2A Power (Watts) 1000	Input Type	Cord
Current - Output (Max) Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 9.2A 9.2A 9.2A 9.2A 201W 00000000000000000000000000000000	Voltage - Input	85 ~ 264 VAC
Power (Watts) 221W No Load Power Consumption 500mW (Max) Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 221W 500mW (Max) - COMMERCIAL STREET ST	Voltage - Output	24V
No Load Power Consumption 500mW (Max) Polarization - ITE (Commercial) Efficiency Level V Operating Temperature 0° C \sim 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Current - Output (Max)	9.2A
Polarization - Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension $8.20^{\circ}\text{L x } 2.90^{\circ}\text{W x } 1.60^{\circ}\text{H } (208.0\text{mm x } 73.0\text{mm x } 39.0\text{mm})$	Power (Watts)	221W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector DIN, 8 Pin Size / Dimension $8.20^{\circ}\text{L x } 2.90^{\circ}\text{W x } 1.60^{\circ}\text{H } (208.0\text{mm x } 73.0\text{mm x } 39.0\text{mm})$	Polarization	-
Operating Temperature 0°C ~ 60°C Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Applications	ITE (Commercial)
Output Connector DIN, 8 Pin Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Efficiency	Level V
Size / Dimension 8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	DIN, 8 Pin
Report errors?	Size / Dimension	8.20" L x 2.90" W x 1.60" H (208.0mm x 73.0mm x 39.0mm)
Report oriois.		Report errors?

FWA220024A-12B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWA220024A-12B Payment Methods



















FWA220024A-12B Shipping Methods













If you have any question about FWA220024A-12B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com