



FWC3018-760F Information



For Reference Only

Part Number FWC3018-760F Manufacturer Inventus Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 18V 30W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWC3018-760F Specifications

Manufacturer Part NumberFWC3018-760FManufacturerInventus PowerCategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesFWC30Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output18VCurrent - Output (Max)1.7APower (Watts)31WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series FWC30 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.7A Power (Watts) 31W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Manufacturer Part Number	FWC3018-760F
Package-SeriesFWC30Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output18VCurrent - Output (Max)1.7APower (Watts)31WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 60°COutput ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Manufacturer	Inventus Power
Package - Series FWC30 Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.7A Power (Watts) 31W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesFWC30Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output $18V$ Current - Output (Max) $1.7A$ Power (Watts) $31W$ No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension 4.25°L L $x 2.50^{\circ}\text{W}$ W $x 1.30^{\circ}\text{H}$ (108.0mm x 34.0mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.7A Power (Watts) 31W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Package	-
Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.7A Power (Watts) 31W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C ~ 60° C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Series	FWC30
Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 18V Current - Output (Max) 1.7A Power (Watts) 31W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25° L x 2.50° W x 1.30° H (108.0mm x 64.5mm x 33.0mm)	Region Utilized	North America
Voltage - Input 85 ~ 264 VAC Voltage - Output 18V Current - Output (Max) 1.7A Power (Watts) No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 85 ~ 264 VAC 18V 85 ~ 264 VAC 18V 1.7A 1.7A 9.0mW (Max) Positive Center ITE (Commercial) Level V Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Form	Desktop (Class I)
Voltage - Output Current - Output (Max) 1.7A Power (Watts) No Load Power Consumption Positive Center Applications ITE (Commercial) Efficiency Operating Temperature O°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 18V 1.7A 1.7A 31W No Load Power Consumption 300mW (Max) Positive Center Level V Operating Temperature O°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Input Type	Cord
Current - Output (Max) 1.7A Power (Watts) 31W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Voltage - Input	85 ~ 264 VAC
Power (Watts) No Load Power Consumption 300mW (Max) Polarization Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 60°C Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Voltage - Output	18V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Current - Output (Max)	1.7A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.25^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.30^{\circ}\text{H} (108.0 \text{mm} \times 64.5 \text{mm} \times 33.0 \text{mm})$	Power (Watts)	31W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.25^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.30^{\circ}\text{H} (108.0\text{mm} \times 64.5\text{mm} \times 33.0\text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.25^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.30^{\circ}\text{H} (108.0\text{mm} \times 64.5\text{mm} \times 33.0\text{mm})$	Polarization	Positive Center
Operating Temperature $0^{\circ}\text{C} \sim 60^{\circ}\text{C}$ Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.25^{\circ}\text{L} \times 2.50^{\circ}\text{W} \times 1.30^{\circ}\text{H} (108.0\text{mm} \times 64.5\text{mm} \times 33.0\text{mm})$	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Efficiency	Level V
Size / Dimension 4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)	Operating Temperature	0°C ~ 60°C
	Output Connector	Barrel Plug, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.25" L x 2.50" W x 1.30" H (108.0mm x 64.5mm x 33.0mm)
		Report errors

FWC3018-760F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWC3018-760F Payment Methods



















FWC3018-760F Shipping Methods













If you have any question about FWC3018-760F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com