

FWJ-80A

FWJ-80A Information



Part Number	FWJ-80A	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE 80AMP 1000V AC SEMI-COND	
Package	Cylindrical, Blade Terminal (Bolt)	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FWJ-80A Specifications

Manufacturer Part NumberFWJ-80AManufacturerEdonCategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWJFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFusator-Class-ApprovalsCE, UROperating Temperature-Mounting TypeBoltMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.25" Diax 3.085" L (28.57mm x 78.36mm)		
CategoryCircuit ProtectionCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWJFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature25KA AC, 50kA DCBreaking Capacity @ Rated VoltageBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Manufacturer Part Number	FWJ-80A
Current RatingElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWJFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage25kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWJFuse TypeCartridgeFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated VoltageSkA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Category	Circuit Protection
SeriesFWJFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated VoltageSok AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeFuse Type60ACurrent Rating60OV (1kV)Voltage Rating - AC800VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Preaking Capacity @ Rated Voltage5kA AC, 50kA DCPockage / CaseCljindrical, Blade Terminal (Bolt)Ste / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating80AVoltage Rating - AC1000V (1kV)Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated VoltageSok ACC, 50k A DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Series	FWJ
Voltage Rating - AC1000V (1kV)Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated VoltageSikA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Fuse Type	Cartridge
Voltage Rating - DC800VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Preaking Capacity @ Rated VoltageStkA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Current Rating	80A
Response Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated VoltageStSA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Voltage Rating - AC	1000V (1kV)
ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage25kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Voltage Rating - DC	800V
Features-Features-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage25kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Response Time	-
Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage25kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Applications	Electrical, Industrial
ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage25kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage25kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Class	-
Breaking Capacity @ Rated Voltage25kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Approvals	CE, UR
Mounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Operating Temperature	-
Package / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Breaking Capacity @ Rated Voltage	25kA AC, 50kA DC
Size / Dimension 1.125" Dia x 3.085" L (28.57mm x 78.36mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.125" Dia x 3.085" L (28.57mm x 78.36mm)
		Report errors?

FWJ-80A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about FWJ-80A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com