

FWP-250 Information



For Reference Only

Part Number FWP-250 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionFUSE BUSS SEMI CONDUCTORPackageCylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWP-250 Specifications

Manufacturer Part NumberFWP-250ManufacturerEatonCategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Manufacturer Part Number	FWP-250
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Category	Circuit Protection
SeriesFWPFuse TypeCartridgeCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating250AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 250A 700V 700V 700V 700V 700V 8esponse Time Fast Semiconductors Feat Voltage Verticals Size / Dimension 200A 700V 700V	Series	FWP
Voltage Rating - AC Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 700	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 700V 700V 700V 700V 8emiconductors Semiconductors	Current Rating	250A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors LR OPERATOR Semiconductors UR Class - Bolt CuR Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Voltage Rating - AC	700V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Cultact - Suppose Semiconductors - Cultact - Suppose Semiconductors - Cultact - Cu	Voltage Rating - DC	700V
Features - Class - Class - UR Approvals UR Operating Temperature - Earth of the Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Response Time	Fast
Class - UR Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Applications	Semiconductors
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR Culture Culture Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Approvals	UR
Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 2.193" L (31.00mm x 55.70mm)
		Report errors?

FWP-250 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWP-250 Payment Methods



















FWP-250 Shipping Methods













If you have any question about FWP-250, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com