

### **FWP-350 Information**



For Reference Only

**Part Number** FWP-350 **Manufacturer** Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE 350A

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **FWP-350 Specifications**

Manufacturer Part NumberFWP-350ManufacturerEatonCategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Manufacturer Part Number	FWP-350
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Category	Circuit Protection
SeriesFWPFuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating350AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension	Series	FWP
Voltage Rating - AC  Voltage Rating - DC  700V  Response Time Fast  Applications Semiconductors  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  700V  700	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Semiconductors  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  700V  700V  700V  700V  700V  8emiconductors  Semiconductors	Current Rating	350A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors  LR OPERATOR  Semiconductors  UR  Class - Bolt CuR  Cylindrical, Blade Terminal (Bolt) 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Voltage Rating - AC	700V
Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Semiconductors  - Cultact  - Suppose Semiconductors  - Cultact  - Suppose Semiconductors  - Cultact  - Cu	Voltage Rating - DC	700V
Features - Class - Class - UR  Approvals UR  Operating Temperature - Earth of the Capacity @ Rated Voltage 200kA  Mounting Type Bolt  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Response Time	Fast
Class - UR  Approvals UR  Operating Temperature -  Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Applications	Semiconductors
Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  UR  Culture  Culture  Cylindrical, Blade Terminal (Bolt)  1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Approvals	UR
Mounting Type  Bolt Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.220" Dia x 2.193" L (31.00mm x 55.70mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.220" Dia x 2.193" L (31.00mm x 55.70mm)
		Report errors?

### **FWP-350 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **FWP-350 Payment Methods**



















### **FWP-350 Shipping Methods**













If you have any question about FWP-350, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com