

### **FWP-40 Information**



For Reference Only

Part Number FWP-40 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionBUSS SEMI CONDUCTOR FUSEPackageCylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **FWP-40 Specifications**

Manufacturer Part NumberFWP-40ManufacturerEatonCategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.126" L (20.60mm x 54.00mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Manufacturer Part Number	FWP-40
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt) Series FWP Fuse Type Cartridge Current Rating 40A Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension  Evaluations FWP Cylindrical, Blade Terminal (Bolt) Cylindrical, Blade Terminal (Bolt) Size / Dimension	Manufacturer	Eaton
Package         Cylindrical, Blade Terminal (Bolt)           Series         FWP           Fuse Type         Cartridge           Current Rating         40A           Voltage Rating - AC         700V           Voltage Rating - DC         700V           Response Time         Fast           Applications         Semiconductors           Features         -           Class         -           Approvals         UR           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA           Mounting Type         Bolt           Package / Case         Cylindrical, Blade Terminal (Bolt)           Size / Dimension         0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Category	Circuit Protection
SeriesFWPFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.811" Dia x 2.126" L (20.60mm x 54.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 40A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  Cartridge A0A Cartridge A0A Cartridge A0A  Voltage Rating - Cartridge A0A  Voltage Rating - AC  700V  Response Time Fast Fast Semiconductors  - Class - Collass - Collidrical, Blade Terminal (Bolt) Size / Dimension  Cartridge A0A  Voltage A0A  Voltage A0A  Cartridge A0A  Voltage Fast Collidrical, Blade Terminal (Bolt) Size / Dimension  Cartridge A0A  Collass - Col	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating  Voltage Rating - AC  700V  Voltage Rating - DC  Response Time  Fast  Applications  Semiconductors  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt  Package / Case  Size / Dimension  40A  40A  40A  40A  40A  40A  40A  40	Series	FWP
Voltage Rating - AC  Voltage Rating - DC  700V  Response Time Fast  Applications Semiconductors  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  700V  8extorminal (Bolt) 700V  70	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Fast  Applications Semiconductors  Features - Class - Approvals UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  700V  700V  700V  700V  8expt 4  Au  Approvals  Cylindrical, Blade Terminal (Bolt) Size / Dimension  700V  8expt 4  Au  Au  Approvals  Cylindrical, Blade Terminal (Bolt)  O.811" Dia x 2.126" L (20.60mm x 54.00mm)	Current Rating	40A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors  - Class - CHANCE  - BRING BRIN	Voltage Rating - AC	700V
Applications  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Semiconductors  - Bemiconductors  - Cylindrical, Blade Terminal (Bolt)  0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Voltage Rating - DC	700V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Applications	Semiconductors
Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  UR  Culture  C	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Bolt  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Approvals	UR
Mounting Type  Bolt  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.811" Dia x 2.126" L (20.60mm x 54.00mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.811" Dia x 2.126" L (20.60mm x 54.00mm)
		Report errors?

#### **FWP-40 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **FWP-40 Payment Methods**





















### **FWP-40 Shipping Methods**













If you have any question about FWP-40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com