

FWP-40B Information



For Reference Only

Part Number FWP-40B **Manufacturer** Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE 40A 700V

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWP-40B Specifications

Manufacturer Part NumberFWP-40BManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.813" Dia x 2.750" L (20.65mm x 69.85mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Manufacturer Part Number	FWP-40B
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWP Fuse Type Cartridge Current Rating 40A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time - Rating Electrical, Industrial Features - Class - C Approvals CE, CSA, UR Operating Temperature - Package Y Rated Voltage Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Category	Circuit Protection
SeriesFWPFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.813" Dia x 2.750" L (20.65mm x 69.85mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating40AVoltage Rating - AC700VVoltage Rating - DC700VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Size / Dimension 40A 40A 40A 40A 40A 40A 40A 40A 40A 40	Series	FWP
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 700	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 700V 700V 700V 700V 700V 700V 8100 6100	Current Rating	40A
Response Time - Applications - Electrical, Industrial - Class - Class - Approvals - CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage - Bolt - Bolt - Clase - Class - CE, CSA, UR	Voltage Rating - AC	700V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Voltage Rating - DC	700V
Features - Class - Class - CE, CSA, UR Operating Temperature - Streaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Response Time	-
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Breaking Capacity @ Rated Voltage	200kA AC, 50kA DC
Size / Dimension 0.813" Dia x 2.750" L (20.65mm x 69.85mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	0.813" Dia x 2.750" L (20.65mm x 69.85mm)
		Report errors?

FWP-40B Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWP-40B Payment Methods



















FWP-40B Shipping Methods













If you have any question about FWP-40B, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com