

FWP-70 Information



For Reference Only

Part Number FWP-70 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE 70A 700V FAST

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWP-70 Specifications

Manufacturer Part Number FWP-70 Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWP Fuse Type Cartridge Current Rating 70A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm) Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesFWPFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Manufacturer Part Number	FWP-70
Beckage Cylindrical, Blade Terminal (Bolt) Series FWP Fuse Type Cartridge Current Rating 70A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension ISBN 1988 Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Category	Circuit Protection
SeriesFWPFuse TypeCartridgeCurrent Rating70AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.063" Dia x 2.126" L (27.00mm x 54.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating70AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 70A 70A 70A 70B 70B 70B 70B 70B	Series	FWP
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 700V 700V 700V 8exponse Time Fast Semiconductors - UR - Class - Cylindrical, Blade Terminal (Bolt) 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Current Rating	70A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors UR 0- Class - Class - Bolt Bolt Cylindrical, Blade Terminal (Bolt) 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Voltage Rating - AC	700V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Semiconductors - Semiconductors Semiconductors - Cultact - Suppose Semiconductors - Cylindrical Semiconductors - Semiconduc	Voltage Rating - DC	700V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Response Time	Fast
Class - UR Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Applications	Semiconductors
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR Culture Culture Cylindrical, Blade Terminal (Bolt) 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Approvals	UR
Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.063" Dia x 2.126" L (27.00mm x 54.00mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.063" Dia x 2.126" L (27.00mm x 54.00mm)
		Report errors?

FWP-70 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWP-70 Payment Methods





















FWP-70 Shipping Methods













If you have any question about FWP-70, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com