

FWP-900 Information



For Reference Only

Part Number FWP-900 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE 90A 700V FAST

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWP-900 Specifications

Manufacturer Part Number FWP-900 Manufacturer Eaton Category Circuit Protection Package Cylindrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWP Fuse Type Cartridge Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesSeriesFWPFuse TypeCartridgeCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Manufacturer Part Number	FWP-900
Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWP Fuse Type Cartridge Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) Size / Dimension Serically Fuses Cutridge Cartridge Cart	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWPFuse TypeCartridgeCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Category	Circuit Protection
SeriesFWPFuse TypeCartridgeCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC700VResponse TimeFastApplicationsSemiconductorsFeatures-Class-ApprovalsUROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBoltPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension3.500" Dia x 3.200" L (88.90mm x 81.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge Cartridge 900A 700V Response Time Fast Semiconductors Feat Fust Fast Fast - College Fast Semiconductors Features - College Fast Semiconductors Features - College Fast Semiconductors Features - College Fast Semiconductors Semiconductors Fast Fast Semiconductors S	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC 700V Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Series	FWP
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Size / Dimension 700V 700V 700V 700V 700V 700V 700V 8exponse Time Fast Semiconductors - UR - Columnation - Columnation Columnati	Fuse Type	Cartridge
Voltage Rating - DC Response Time Fast Applications Semiconductors Features - Class - Approvals UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 700V 700V 700V 8exponse Time Fast Semiconductors - UR - Class - Cylindrical, Blade Terminal (Bolt) Size / Dimension 700V 8exponse Time Fast Semiconductors -	Current Rating	900A
Response Time Applications Semiconductors Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Fast Semiconductors - Class - CHANCE - BRICK Semiconductors - UR UR CUR CUR CUR CUR CUR CUR	Voltage Rating - AC	700V
Applications Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Semiconductors - Bemiconductors - Cylindrical, Blade Terminal (Bolt) Size / Dimension Size / Dimension Semiconductors - Cylindrical, Blade Terminal (Bolt) Size / Dimension Size / Dimension Size / Dimension	Voltage Rating - DC	700V
Features - Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Response Time	Fast
Class - Approvals UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Applications	Semiconductors
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension UR Culture Culture Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Approvals	UR
Mounting Type Bolt Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 3.500" Dia x 3.200" L (88.90mm x 81.00mm)	Mounting Type	Bolt
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	3.500" Dia x 3.200" L (88.90mm x 81.00mm)
		Report errors?

FWP-900 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWP-900 Payment Methods





















FWP-900 Shipping Methods













If you have any question about FWP-900, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com