



FWX-1A14F Information

www.heisener.ca

For Reference Only

Part Number FWX-1A14F

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 1A 250VAC/DC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWX-1A14F Specifications

Manufacturer Part NumberFWX-1A14FManufacturerEatonCategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesFWXFuse TypeCartridgeCurrent Rating1AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFWXFuse TypeCartridgeCurrent Rating1AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer Part Number	FWX-1A14F
Package Cartridge, Non-Standard Series FWX Fuse Type Cartridge Current Rating 1A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - 2 Applications Electrical, Industrial Features - C Class - C Approvals - C Operating Temperature - S Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer	Eaton
Package Cartridge, Non-Standard Series FWX Fuse Type Cartridge Current Rating 1A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection
SeriesFWXFuse TypeCartridgeCurrent Rating1AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating1AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 1A A 14	Series	FWX
Voltage Rating - AC Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 250V 250V 260V 26	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V Electrical, Industrial	Current Rating	1A
Response Time - General Features - Glass - Gla	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	250V
Features - Class - Class - Coperating Temperature - Coperating Capacity @ Rated Voltage 200kA AC, 50kA DC Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	-
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 200kA AC, 50kA DC Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension O.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 50kA DC
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)
		Report errors?

FWX-1A14F Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWX-1A14F Payment Methods


































If you have any question about FWX-1A14F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com