

FWX-300A Information

sener.com

Part Number FWX-300A Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 300A 250VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









FWX-300A Specifications

Manufacturer Part NumberFWX-300AManufacturerEatonCategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWXFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 3.840" L (38.10mm x 97.54mm)		
Category Circuit Protection Electrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FWX Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Circuit Protection Electrical, Specialty Fuses Electrical, Industrial CE, CSA, UR CO, CSA,	Manufacturer Part Number	FWX-300A
Beaking Capacity @ Rated Voltage Electrical, Specialty Fuses Cylindrical, Blade Terminal (Bolt) FWX Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses FWX Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Capto Cattridge Capto Cattridge Capto Cattridge Capto	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWXFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Category	Circuit Protection
Fuse Type Cartridge Current Rating 300A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Cartridge Applications Electrical, Industrial Features - Class - CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 300A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge 250V Cartridge AnouA CE, CSA Cartridge Cartridge Case Cartridge AnouA Cose Cartridge AnouA Cartridge AnouA Cose Cose Capacity @ Rated Voltage Capacity @ Rated Voltage Colindrical, Blade Terminal (Bolt) Size / Dimension Cartridge AnouA Capacity @ Cartridge Capacity @ Capacity & Capac	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 300A 250V 250V 250V Electrical (Industrial) - CE, CSA, UR - CE, CSA, UR CE, CSA, UR CUR CUR CUR CUR CUR CUR CUR	Series	FWX
Voltage Rating - AC Voltage Rating - DC 250V Response Time Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 250V 250V 250V 260V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 250V 250V 250V 260V 26	Current Rating	300A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Clestrical, Industrial - CE, CSA, UR CE,	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Voltage Rating - DC	250V
Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Response Time	-
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Approvals	CE, CSA, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Breaking Capacity @ Rated Voltage	200kA AC, 50kA DC
Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 3.840" L (38.10mm x 97.54mm)
		Report errors?

FWX-300A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

FWX-300A Payment Methods





















FWX-300A Shipping Methods













If you have any question about FWX-300A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com