

### **FWX-400A Information**

sener.com

Part Number FWX-400A Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CARTRIDGE 400A 250VAC/VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **FWX-400A Specifications**

Manufacturer Part NumberFWX-400AManufacturerEatonCategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFWXFuse TypeCartridgeCurrent Rating400AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 3.840" L (38.10mm x 97.54mm)Report errors?		
Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cylindrical, Blade Terminal (Bolt)  FWX  Fuse Type  Cartridge  Current Rating  400A  Voltage Rating - AC  250V  Voltage Rating - DC  250V  Response Time  - Applications  Electrical, Industrial  Features  - Class  - CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  Circuit Protection  Electrical, Specialty Fuses  Cartridge  Cartri	Manufacturer Part Number	FWX-400A
Electrical, Specialty Fuses  Package Cylindrical, Blade Terminal (Bolt)  Series FWX  Fuse Type Cartridge  Current Rating 400A  Voltage Rating - AC 250V  Voltage Rating - DC 250V  Response Time - Applications Electrical, Industrial  Features - Class - C  Approvals CE, CSA, UR  Operating Temperature - Breaking Capacity @ Rated Voltage COKA AC, 50kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFWXFuse TypeCartridgeCurrent Rating400AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Category	Circuit Protection
SeriesFWXFuse TypeCartridgeCurrent Rating400AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 3.840" L (38.10mm x 97.54mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating400AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension  400A 400A 400A 400A 400A 400A 400A 40	Series	FWX
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  - Applications  Electrical, Industrial  Features  - Class  - Approvals  CE, CSA, UR  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  250V  250V  250V  260V  260	Fuse Type	Cartridge
Voltage Rating - DC  Response Time - Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UR  Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension  250V Electrical (Industrial) Electrical, Industrial - CE, CSA, UR - CE, CSA, UR CE, CSA, UR CE, CSA, UR CYLindrical, Blade Terminal (Bolt) CYLINDRICAL (38.10mm x 97.54mm)	Current Rating	400A
Response Time - Applications - Electrical, Industrial - Class - Class - Approvals - CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage - Bolt Mount - Package / Case - Cylindrical, Blade Terminal (Bolt) - Size / Dimension - CE, CSA, UR	Voltage Rating - AC	250V
Applications Electrical, Industrial  Features - Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Voltage Rating - DC	250V
Features - Class - Class - CE, CSA, UR  Approvals CE, CSA, UR  Operating Temperature - Estating Capacity @ Rated Voltage 200kA AC, 50kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Response Time	-
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 50kA DC  Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC  Mounting Type Bolt Mount  Package / Case Cylindrical, Blade Terminal (Bolt)  Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Approvals	CE, CSA, UR
Mounting Type  Bolt Mount  Package / Case  Cylindrical, Blade Terminal (Bolt)  Size / Dimension  1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Breaking Capacity @ Rated Voltage	200kA AC, 50kA DC
Size / Dimension 1.500" Dia x 3.840" L (38.10mm x 97.54mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 3.840" L (38.10mm x 97.54mm)
		Report errors?

#### **FWX-400A Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **FWX-400A Payment Methods**



















## **FWX-400A Shipping Methods**













If you have any question about FWX-400A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com