

### **FWX-4A14F Information**

www.heisener.ca

Part Number FWX-4A14F

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** FUSE CRTRDGE 4A 250VAC/DC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **FWX-4A14F Specifications**

Manufacturer Part Number  Manufacturer  Eaton  Category  Circuit Protection  Electrical, Specialty Fuses  Package  Cartridge, Non-Standard  Series  FWX  Fuse Type  Cartridge  Current Rating  Voltage Rating - AC  Voltage Rating - DC  Response Time  Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  Eaton  Circuit Protection  Electrical, Specialty Fuses  FWX  Cartridge, Non-Standard  Electrical, Industrial  Fountier Temperature  Function  Function  Function  Cartridge  Cartridge, Non-Standard  Cartridge, Non-Standard  Cartridge, Non-Standard  Function  Funct			
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesFWXFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer Part Number	FWX-4A14F	
Package Cartridge, Non-Standard Series FWX Fuse Type Cartridge Current Rating 4A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time - 2 Applications Electrical, Industrial Features - C Class - C Approvals - C Operating Temperature - S Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Manufacturer	Eaton	
Package         Cartridge, Non-Standard           Series         FWX           Fuse Type         Cartridge           Current Rating         4A           Voltage Rating - AC         250V           Voltage Rating - DC         250V           Response Time         -           Applications         Electrical, Industrial           Features         -           Class         -           Approvals         -           Operating Temperature         -           Breaking Capacity @ Rated Voltage         200kA AC, 50kA DC           Mounting Type         Holder           Package / Case         Cartridge, Non-Standard           Size / Dimension         0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Category	Circuit Protection	
SeriesFWXFuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)		Electrical, Specialty Fuses	
Fuse TypeCartridgeCurrent Rating4AVoltage Rating - AC250VVoltage Rating - DC250VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kA AC, 50kA DCMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Package	Cartridge, Non-Standard	
Current Rating Voltage Rating - AC 250V  Voltage Rating - DC 250V  Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  4A  4A  4A  4A  250V  250V  Response Time -  Relectrical, Industrial -  200KA AC, 50KA DC  Holder  Cartridge, Non-Standard Size / Dimension  50.563" Dia x 2.000" L (14.30mm x 50.80mm)	Series	FWX	
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  - Applications  Electrical, Industrial  Features  - Class  - Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  250V  250V  250V  250V  260V  26	Fuse Type	Cartridge	
Voltage Rating - DC  Response Time - Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  250V  Electrical, Industrial - Class - Coverating Industrial - Coverating Indus	Current Rating	4A	
Response Time - Applications Electrical, Industrial  Features - Class	Voltage Rating - AC	250V	
Applications Electrical, Industrial  Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Voltage Rating - DC	250V	
Features - Class - Class - Coperating Temperature - Coperating Capacity @ Rated Voltage 200kA AC, 50kA DC Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Response Time	-	
Class - Approvals - Coperating Temperature - Seraking Capacity @ Rated Voltage 200kA AC, 50kA DC Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Applications	Electrical, Industrial	
Approvals  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  O.563" Dia x 2.000" L (14.30mm x 50.80mm)	Features	-	
Operating Temperature  Breaking Capacity @ Rated Voltage  200kA AC, 50kA DC  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Class	-	
Breaking Capacity @ Rated Voltage 200kA AC, 50kA DC  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Approvals	-	
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Operating Temperature	-	
Package / Case Cartridge, Non-Standard Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA AC, 50kA DC	
Size / Dimension 0.563" Dia x 2.000" L (14.30mm x 50.80mm)	Mounting Type	Holder	
· · · · · · · · · · · · · · · · · · ·	Package / Case	Cartridge, Non-Standard	
D 0	Size / Dimension	0.563" Dia x 2.000" L (14.30mm x 50.80mm)	
Report errors?			Report errors?

#### **FWX-4A14F Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **FWX-4A14F Payment Methods**





















## **FWX-4A14F Shipping Methods**













If you have any question about FWX-4A14F, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com