

FX30B-3P-7.62DSA30

FX30B-3P-7.62DSA30 Information



Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



FX30B-3P-7.62DSA30 Specifications

Manufacturer Part Number	FX30B-3P-7.62DSA30
Manufacturer	Hirose Electric Co Ltd
Category	Connectors, Interconnects
	Rectangular Connectors - Headers, Male Pins
Package	-
Series	FunctionMax? FX30B
Connector Type	Header
Contact Type	Male Blade
Pitch - Mating	0.300" (7.62mm)
Style	Board to Board
Shrouding	Shrouded - 2 Wall
Number of Positions	3
Number of Positions Loaded	All
Number of Rows	1
Row Spacing - Mating	-
Mounting Type	Through Hole
Termination	Solder
Fastening Type	Push-Pull
Contact Length - Mating	-
Contact Length - Post	0.130" (3.30mm)
Overall Contact Length	-
Insulation Height	0.953" (24.20mm)
Contact Shape	Rectangular
Contact Finish - Mating	Gold

Contact Finish Thickness - Mating	3.9µin (0.10µm)
Contact Finish - Post	Tin
Contact Material	Copper Alloy
Insulation Material	Polyamide (PA), Nylon
Features	Board Guide, Board Lock
Operating Temperature	-55°C ~ 105°C
Ingress Protection	-
Material Flammability Rating	UL94 V-0
Insulation Color	Black
	Report errors?

FX30B-3P-7.62DSA30 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

FX30B-3P-7.62DSA30 Payment Methods



If you have any question about FX30B-3P-7.62DSA30, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com