

G17K15003101EU

G17K15003101EU Information

Contraction of the second seco	 G17K15003101EU Amphenol Commercial Products Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 15POS STR IDC - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G17K15003101EU Specifications

ManufacturerAmphenol Commercial ProductsCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesG17KConnector StyleD-Sub ConnectorsConnector TypeReceptacle, Female SocketsNumber of Positions15Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FeaturesStellShell Material, FinishSteelContact Finish Thickness-Contact Finish Thic		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesG17KConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FerninationDC, Ribbon CableFeaturesSteelShell Material, FinishSteelContact Finish Thickness-Contact Finish Thickness-Material Flammability RatingUL94 V-0	Manufacturer Part Number	G17K15003101EU
D-Sub ConnectorsPackage-SeriesG17KConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMuunting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact Finish Thickness-Contact Finish Thickness-Material Flammability RatingUL94 V-0	Manufacturer	Amphenol Commercial Products
Package-SeriesG17KConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector LayoutQ (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FerminationIDC, Ribbon CableFeaturesSeelContact FinishSteelContact FinishGoldContact Finish Thickness-Auterial Flammability RatingUL94 V-0	Category	Connectors, Interconnects
SeriesG17KConnector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact Finish Thickness-Contact Finish Thickness-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact Finish Thickness-Contact Finish Thickness-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact Finish Thickness-Contact Finish Thickness-Material Flammability RatingUL94 V-0	Series	G17K
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FerminationDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact Finish Thickness-Contact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypeFree Hanging (In-Line)Fange FeaturesHousing/Shell (Unthreaded)FeaturesIDC, Ribbon CableShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypeFree Hanging (In-Line)Flange FeatureHousing/Shell (Unthreaded)FerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureHousing/Shell (Unthreaded)TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationIDC, Ribbon CableFeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Free Hanging (In-Line)
FeaturesFeed Through, Strain ReliefShell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteelContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Termination	IDC, Ribbon Cable
Contact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Features	Feed Through, Strain Relief
Contact Finish Thickness-Ingress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	-
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

G17K15003101EU Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G17K15003101EU Payment Methods





If you have any question about G17K15003101EU, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com