

## **G2A-432A DC12 Information**

Heisener.com

Part Number G2A-432A DC12

Manufacturer Omron Automation and Safety

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE 4PDT 500MA 12V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2A-432A DC12 Specifications**

Manufacturer         G2A-432A DC12           Manufacturer         Omron Automation and Safety           Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         G2A           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         88mA           Coil Voltage         12VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         500mA           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         15ms           Release Time         15ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In		
CategoryRelaysPackage-SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	G2A-432A DC12
Package-SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         G2A           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         88mA           Coil Voltage         12VDC           Contact Form         4PDT (4 Form C)           Contact Rating (Current)         500mA           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         9.6 VDC           Turn Off Voltage (Min)         1.2 VDC           Operate Time         15ms           Release Time         15ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current88mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 88mA Coil Voltage 12VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current88mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	G2A
Coil Current88mACoil Voltage12VDCContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 12VDC  Contact Form 4PDT (4 Form C)  Contact Rating (Current) 500mA  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 15ms  Release Time 15ms  Features - Mounting Type Socketable  Termination Style Plug In	Coil Type	Non Latching
Contact Form 4PDT (4 Form C)  Contact Rating (Current) 500mA  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 15ms  Release Time 15ms  Release Time 15ms  Features	Coil Current	88mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1.2 VDC  Operate Time  15ms  Release Time  15ms  Features  -  Mounting Type  Socketable  Termination Style  Flug In	Coil Voltage	12VDC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC  Operate Time 15ms  Release Time 15ms  Features -  Mounting Type Socketable  Termination Style Plug In	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max)  7 Turn Off Voltage (Min)  9.6 VDC  1.2 VDC  Operate Time  15 ms  Release Time  15 ms  Features  -  Mounting Type  Socketable  Termination Style  Plug In	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  - Mounting Type  Socketable  Termination Style  1.2 VDC  15ms  Socketable  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	9.6 VDC
Release Time 15ms  Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	1.2 VDC
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	15ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
•		Report errors?

#### **G2A-432A DC12 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G2A-432A DC12 Payment Methods**



















### **G2A-432A DC12 Shipping Methods**













If you have any question about G2A-432A DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com