

G2A-432A-DC48 Information

Heisener.com

Part Number G2A-432A-DC48

Manufacturer Omron Automation and Safety

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY GEN PURPOSE 4PDT 500MA 48V

Package


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com





Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2A-432A-DC48 Specifications

Manufacturer Part Number G2A-432A-DC48 Manufacturer Omron Automation and Safety Category Relays Package - Series G2A Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable		
CategoryRelaysPackage-SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current22mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Manufacturer Part Number	G2A-432A-DC48
Package - Series G2A Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable	Manufacturer	Omron Automation and Safety
Package - G2A Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable	Category	Relays
Series G2A Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 22mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features - Mounting Type Socketable	Package	-
Coil TypeNon LatchingCoil Current22mACoil Voltage48VDCContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)4.8 VDCOperate Time15msRelease Time15msFeatures-Mounting TypeSocketable	Series	G2A
Coil Current 22mA Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Release Time 15ms Features Mounting Type Socketable	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features Mounting Type Socketable	Coil Type	Non Latching
Contact Form 4PDT (4 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features Mounting Type Socketable	Coil Current	22mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) 4.8 VDC Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable	Contact Form	4PDT (4 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features - Mounting Type 38.4 VDC 4.8 VDC 15ms 5ocketable	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable	Switching Voltage	250VAC, 125VDC - Max
Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable	Turn On Voltage (Max)	38.4 VDC
Release Time 15ms Features - Mounting Type Socketable	Turn Off Voltage (Min)	4.8 VDC
Features - Mounting Type Socketable	Operate Time	15ms
Mounting Type Socketable	Release Time	15ms
	Features	-
	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

G2A-432A-DC48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2A-432A-DC48 Payment Methods



















G2A-432A-DC48 Shipping Methods













If you have any question about G2A-432A-DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com