

G2A-432A-N-AC100/110

G2A-432A-N-AC100/110 Information

| Heisener.com | G2A-432A-N-AC100/110 Omron Automation and Safety Relays Signal Relays, Up to 2 Amps RELAY GEN PUR 4PDT 500MA 110V - For the pricing/inventory/lead time, please contact | |
|--------------------|---|-----------------|
| For Reference Only | us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2A-432A-N-AC100/110 Specifications

| Manufacturer Part NumberG2A-432A-N-AC100/110ManufacturerOmron Automation and SafetyCategoryRelaysCategorySignal Relays, Up to 2 AmpsPackage-SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Voltage10VACContact Form4PDT (4 Form C)Contact Rating (Current)SowAC, 125VDC - MaxSwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)33 VACOperate Time15msRelase Time15msFeaturesLED IndicatorMonting TypeDow In | | |
|---|--------------------------|-----------------------------|
| CategoryRelaysCategorySignal Relays, Up to 2 AmpsPackage-SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14mACoil Voltage110VACContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease TimeLED IndicatorMounting TypeSocketable | Manufacturer Part Number | G2A-432A-N-AC100/110 |
| Number of the sector of the | Manufacturer | Omron Automation and Safety |
| Package-SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14mACoil Voltage110VACContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Category | Relays |
| SeriesG2ARelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14mACoil Voltage110VACContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | | Signal Relays, Up to 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current14mACoil Voltage110VACContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Package | - |
| Coil TypeNon LatchingCoil Current14mACoil Voltage110VACContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Series | G2A |
| Coil Current14mACoil Voltage110VACContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Relay Type | General Purpose |
| Coil Voltage110VACContact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Coil Type | Non Latching |
| Contact Form4PDT (4 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Coil Current | 14mA |
| Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Coil Voltage | 110VAC |
| Switching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Contact Form | 4PDT (4 Form C) |
| Turn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Contact Rating (Current) | 500mA |
| Turn Off Voltage (Min)33 VACOperate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Switching Voltage | 250VAC, 125VDC - Max |
| Operate Time15msRelease Time15msFeaturesLED IndicatorMounting TypeSocketable | Turn On Voltage (Max) | 88 VAC |
| Release Time15msFeaturesLED IndicatorMounting TypeSocketable | Turn Off Voltage (Min) | 33 VAC |
| FeaturesLED IndicatorMounting TypeSocketable | Operate Time | 15ms |
| Mounting Type Socketable | Release Time | 15ms |
| | Features | LED Indicator |
| Tormination Stula | Mounting Type | Socketable |
| Plug In | Termination Style | Plug In |
| Report erro | | Report errors? |

G2A-432A-N-AC100/110 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2A-432A-N-AC100/110 Payment Methods





If you have any question about G2A-432A-N-AC100/110, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com