



### **G2AK-232A-DC24 Information**

Heisener.com

Part Number G2AK-232A-DC24

Manufacturer Omron Automation and Safety

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 500MA 24V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **G2AK-232A-DC24 Specifications**

Manufacturer Part NumberG2AK-232A-DC24ManufacturerOmron Automation and SafetyCategoryRelaysPackage-SeriesG2AKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current85mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketable		
CategoryRelaysPackage-SeriesG2AKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current85mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-	Manufacturer Part Number	G2AK-232A-DC24
Package - Series G2AK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 85mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features -	Manufacturer	Omron Automation and Safety
Package - Series G2AK Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 85mA Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features	Category	Relays
SeriesG2AKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current85mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current85mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-	Package	-
Coil TypeLatching, Dual CoilCoil Current85mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-	Series	G2AK
Coil Current85mACoil Voltage24VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features -	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current) 500mA  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) -  Operate Time 15ms  Release Time 15ms  Features -	Coil Current	85mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  19.2 VDC  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  -	Coil Voltage	24VDC
Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 19.2 VDC  Turn Off Voltage (Min) -  Operate Time 15ms  Release Time 15ms  Features -	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  -	Contact Rating (Current)	500mA
Turn Off Voltage (Min) Operate Time 15ms Release Time 15ms Features -	Switching Voltage	250VAC, 125VDC - Max
Operate Time 15ms Release Time 15ms Features -	Turn On Voltage (Max)	19.2 VDC
Release Time 15ms Features -	Turn Off Voltage (Min)	-
Features -	Operate Time	15ms
	Release Time	15ms
Mounting Type Socketable	Features	-
	Mounting Type	Socketable
Termination Style Plug In	Termination Style	Plug In
Report errors?		Report errors?

#### **G2AK-232A-DC24** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G2AK-232A-DC24 Payment Methods**



















# **G2AK-232A-DC24** Shipping Methods













If you have any question about G2AK-232A-DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com