



#### **G2AK-234A DC48 Information**

Heisener.com

Part Number G2AK-234A DC48

Manufacturer Omron Automation and Safety

**Category** Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE DPDT 500MA 48V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G2AK-234A DC48 Specifications**

Manufacturer Part Number         G2AK-234A DC48           Manufacturer         Omron Automation and Safety           Category         Relays           Signal Relays, Up to 2 Amps           Package         -           Series         G2AK           Relay Type         General Purpose           Coil Type         Latching, Dual Coil           Coil Current         44mA           Coil Voltage         48VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         500mA           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         38.4 VDC           Turn Off Voltage (Min)         -           Operate Time         15ms           Release Time         15ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In		
CategoryRelaysPackage-SeriesG2AKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	G2AK-234A DC48
Package-SeriesG2AKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package         -           Series         G2AK           Relay Type         General Purpose           Coil Type         Latching, Dual Coil           Coil Current         44mA           Coil Voltage         48VDC           Contact Form         DPDT (2 Form C)           Contact Rating (Current)         500mA           Switching Voltage         250VAC, 125VDC - Max           Turn On Voltage (Max)         38.4 VDC           Turn Off Voltage (Min)         -           Operate Time         15ms           Release Time         15ms           Features         -           Mounting Type         Socketable           Termination Style         Plug In	Category	Relays
SeriesG2AKRelay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current44mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In		Signal Relays, Up to 2 Amps
Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 44mA Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeLatching, Dual CoilCoil Current44mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Series	G2AK
Coil Current44mACoil Voltage48VDCContact FormDPDT (2 Form C)Contact Rating (Current)500mASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)38.4 VDCTurn Off Voltage (Min)-Operate Time15msRelease Time15msFeatures-Mounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 48VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 500mA Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current) 500mA  Switching Voltage 250VAC, 125VDC - Max  Turn On Voltage (Max) 38.4 VDC  Turn Off Voltage (Min) -  Operate Time 15ms  Release Time 15ms  Release Time 15ms  Features  Mounting Type Socketable  Termination Style Plug In	Coil Current	44mA
Contact Rating (Current)  Switching Voltage  250VAC, 125VDC - Max  Turn On Voltage (Max)  38.4 VDC  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  -  Mounting Type  Socketable  Termination Style  Flug In	Coil Voltage	48VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 38.4 VDC Turn Off Voltage (Min) - Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  - Mounting Type  Socketable  Termination Style  38.4 VDC  -  15ms  15ms  Plug In	Contact Rating (Current)	500mA
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  15ms  Features  - Mounting Type  Socketable  Termination Style  Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 15ms Release Time 15ms Features - Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	38.4 VDC
Release Time 15ms  Features - Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	-
Features - Mounting Type Socketable Termination Style Plug In	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In	Release Time	15ms
Termination Style Plug In	Features	-
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

#### **G2AK-234A DC48 Guarantees**



# **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G2AK-234A DC48 Payment Methods**





















# **G2AK-234A DC48 Shipping Methods**













If you have any question about G2AK-234A DC48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com