

Heisener.com

## G2E-184P-H-M-US-DC12

### G2E-184P-H-M-US-DC12 Information

Part Number G2E-184P-H-M-US-DC12

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY GEN PURPOSE SPDT 1A 12V

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# G2E-184P-H-M-US-DC12 Specifications

Manufacturer Part Number  Manufacturer  Omron Electronics Inc-EMC Div  Relays  Signal Relays, Up to 2 Amps  Package  - Series  G2E  Relay Type  General Purpose  Coil Type  Non Latching  Coil Current  17.1mA  Coil Voltage  12VDC  Contact Form  SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 60VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operator Time  2000  Contact Time  American Amplication  Omron Electronics Inc-EMC Div  Relays  Signal Relays, Up to 2 Amps  Figure  General Purpose  General Purpose  Amplication  Special Purpose  17.1mA  17.1mA  12 VDC  14  Switching Voltage  125VAC, 60VDC - Max  Turn Off Voltage (Min)  1.2 VDC		
CategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesG2ERelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current17.1mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)1ASwitching Voltage125VAC, 60VDC - MaxTurn On Voltage (Max)9.6 VDCTurn Off Voltage (Min)1.2 VDC	Manufacturer Part Number	G2E-184P-H-M-US-DC12
Package - Series G2E Relay Type General Purpose Coil Type Non Latching Coil Current 17.1mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC	Manufacturer	Omron Electronics Inc-EMC Div
Package - G2E  Relay Type General Purpose  Coil Type Non Latching  Coil Current 17.1mA  Coil Voltage 12VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 60VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC	Category	Relays
Series G2E  Relay Type General Purpose  Coil Type Non Latching  Coil Current 17.1mA  Coil Voltage 12VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 60VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC		Signal Relays, Up to 2 Amps
Relay Type Coil Type Non Latching Coil Current 17.1mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC	Package	-
Coil Type Non Latching Coil Current 17.1mA Coil Voltage 12VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 1A Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC	Series	G2E
Coil Current 17.1mA  Coil Voltage 12VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 60VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC	Relay Type	General Purpose
Coil Voltage 12VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 1A  Switching Voltage 125VAC, 60VDC - Max  Turn On Voltage (Max) 9.6 VDC  Turn Off Voltage (Min) 1.2 VDC	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  Switching Voltage  125VAC, 60VDC - Max  Turn On Voltage (Max)  7urn Off Voltage (Min)  1.2 VDC	Coil Current	17.1mA
Contact Rating (Current)  Switching Voltage  125VAC, 60VDC - Max  Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1.2 VDC	Coil Voltage	12VDC
Switching Voltage 125VAC, 60VDC - Max Turn On Voltage (Max) 9.6 VDC Turn Off Voltage (Min) 1.2 VDC	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  9.6 VDC  Turn Off Voltage (Min)  1.2 VDC	Contact Rating (Current)	1A
Turn Off Voltage (Min) 1.2 VDC	Switching Voltage	125VAC, 60VDC - Max
	Turn On Voltage (Max)	9.6 VDC
Omerate Time	Turn Off Voltage (Min)	1.2 VDC
Operate Time /ms	Operate Time	7ms
Release Time 3ms	Release Time	3ms
Features -	Features	-
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

### G2E-184P-H-M-US-DC12 Guarantees



#### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### G2E-184P-H-M-US-DC12 Payment Methods



















## G2E-184P-H-M-US-DC12 Shipping Methods













If you have any question about G2E-184P-H-M-US-DC12, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com