

## G2R-1-E-ASI-T130 DC24

### G2R-1-E-ASI-T130 DC24 Information



For Reference Only

**Part Number** G2R-1-E-ASI-T130 DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPDT 16A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G2R-1-E-ASI-T130 DC24 Specifications**

Manufacturer Part Number         G2R-1-E-ASI-T130 DC24           Manufacturer         Omron Electronics Inc-EMC Div           Category         Relays           Power Relays, Over 2 Amps         -           Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         21.8mA           Coil Voltage         24VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         16A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         16.8 VDC           Turn Off Voltage (Min)         3.6 VDC           Operate Time         15ms           Release Time         5ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current21.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-1-E-ASI-T130 DC24
Package Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Termination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package         -           Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         21.8mA           Coil Voltage         24VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         16A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         16.8 VDC           Turn Off Voltage (Min)         3.6 VDC           Operate Time         15ms           Release Time         5ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin	Category	Relays
Series         G2R           Relay Type         General Purpose           Coil Type         Non Latching           Coil Current         21.8mA           Coil Voltage         24VDC           Contact Form         SPDT (1 Form C)           Contact Rating (Current)         16A           Switching Voltage         380VAC, 125VDC - Max           Turn On Voltage (Max)         16.8 VDC           Turn Off Voltage (Min)         3.6 VDC           Operate Time         15ms           Release Time         5ms           Features         Sealed - Flux Protection           Mounting Type         Through Hole           Termination Style         PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 21.8mA  Coil Voltage 24VDC  Contact Form SPDT (1 Form C)  Contact Rating (Current) 16A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 16.8 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 15ms  Release Time 5ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current21.8mACoil Voltage24VDCContact FormSPDT (1 Form C)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)16.8 VDCTurn Off Voltage (Min)3.6 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPDT (1 Form C)  Contact Rating (Current)  16A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min) 3.6 VDC  Operate Time 15ms  Release Time 5ms  Release Time 5ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	21.8mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Voltage	24VDC
Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  16.8 VDC  Turn Off Voltage (Min)  3.6 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	16.8 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	3.6 VDC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Papart arrors?	Termination Style	PC Pin
Report errors?		Report errors?

### G2R-1-E-ASI-T130 DC24 Guarantees



### **Ouality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **G2R-1-E-ASI-T130 DC24 Payment Methods**



















## **G2R-1-E-ASI-T130 DC24 Shipping Methods**













If you have any question about G2R-1-E-ASI-T130 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com