

G2R-1-S AC120(S)

G2R-1-S AC120(S) Information



| Part Number | G2R-1-S AC120(S) | |
|--------------|--|--|
| Manufacturer | Omron Automation and Safety | |
| Category | Relays Power Relays, Over 2 Amps | |
| Description | RELAY GEN PURPOSE SPDT 10A 120V | |
| Package | - | |
| | For the pricing/inventory/lead time, please contact us | |
| | Website: https://www.heisener.com | |
| | E-mail: salesdept@heisener.com | |



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2R-1-S AC120(S) Specifications

| ManufacturerOmron Automation and SafetyCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACotact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACCoperate Time10msRelease Time10ms | | |
|---|--------------------------|---|
| CategoryRelaysPackage-Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage (Max)96 VACTurn On Voltage (Max)36 VACOperate Time15msRelease Time10ms | Manufacturer Part Number | G2R-1-S AC120(S) |
| PackagePower Relays, Over 2 AmpsPackage-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage (Max)96 VACTurn On Voltage (Max)96 VACOperate Time15msRelease Time10msFeatures- | Manufacturer | Omron Automation and Safety |
| Package-SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACOperate Time15msRelease Time10ms | Category | Relays |
| SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage (Max)96 VACTurn On Voltage (Max)36 VACOperate Time15msRelease Time-Features- | | Power Relays, Over 2 Amps |
| Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage (Max)96 VACTurn On Voltage (Max)36 VACOperate Time15msRelease Times- | Package | - |
| Coil TypeNon LatchingCoil Current7.5mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Series | G2RS |
| Coil Current7.5mACoil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Relay Type | General Purpose |
| Coil Voltage120VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Coil Type | Non Latching |
| Contact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Coil Current | 7.5mA |
| Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Coil Voltage | 120VAC |
| Switching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Contact Form | SPDT (1 Form C) |
| Turn On Voltage (Max)96 VACTurn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Contact Rating (Current) | 10A |
| Turn Off Voltage (Min)36 VACOperate Time15msRelease Time10msFeatures- | Switching Voltage | 440VAC, 125VDC - Max |
| Operate Time 15ms Release Time 10ms Features - | Turn On Voltage (Max) | 96 VAC |
| Release Time 10ms Features - | Turn Off Voltage (Min) | 36 VAC |
| Features - | Operate Time | 15ms |
| | Release Time | 10ms |
| Mounting Type Socketable | Features | - |
| Socketable | Mounting Type | Socketable |
| Termination StylePlug In, Quick Connect - 0.187" (4.7mm) | Termination Style | Plug In, Quick Connect - 0.187" (4.7mm) |
| Report errors? | | Report errors? |

G2R-1-S AC120(S) Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1-S AC120(S) Payment Methods



G2R-1-S AC120(S) Shipping Methods



If you have any question about G2R-1-S AC120(S), please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com