

G2R-1-SD DC6(S) Information



For Reference Only

Part Number G2R-1-SD DC6(S)

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 6V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-1-SD DC6(S) Specifications

Manufacturer Part Number G2R-1-SD DC6(S) Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm) Report errors?		
Category Relays Power Relays, Over 2 Amps Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Manufacturer Part Number	G2R-1-SD DC6(S)
Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Manufacturer	Omron Automation and Safety
Package - Series G2RS Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Category	Relays
SeriesG2RSRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiodeMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 87mA Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Package	-
Coil TypeNon LatchingCoil Current87mACoil Voltage6VDCContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage440VAC, 125VDC - MaxTurn On Voltage (Max)4.2 VDCTurn Off Voltage (Min)0.9 VDCOperate Time15msRelease Time20msFeaturesDiodeMounting TypeSocketableTermination StylePlug In, Quick Connect - 0.187" (4.7mm)	Series	G2RS
Coil Current Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Relay Type	General Purpose
Coil Voltage 6VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style	Coil Current	87mA
Contact Rating (Current) Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Coil Voltage	6VDC
Switching Voltage 440VAC, 125VDC - Max Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 4.2 VDC Turn Off Voltage (Min) 0.9 VDC Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Switching Voltage	440VAC, 125VDC - Max
Operate Time 15ms Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn On Voltage (Max)	4.2 VDC
Release Time 20ms Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Turn Off Voltage (Min)	0.9 VDC
Features Diode Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Operate Time	15ms
Mounting Type Socketable Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Release Time	20ms
Termination Style Plug In, Quick Connect - 0.187" (4.7mm)	Features	Diode
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In, Quick Connect - 0.187" (4.7mm)
		Report errors?

G2R-1-SD DC6(S) Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1-SD DC6(S) Payment Methods



















G2R-1-SD DC6(S) Shipping Methods













If you have any question about G2R-1-SD DC6(S), please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com