



G2R-1-SKVD-AC220 Information



For Reference Only

Part Number G2R-1-SKVD-AC220

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 10A 220V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-1-SKVD-AC220 Specifications

Manufacturer Part Number G2R-1-SKVD-AC220 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.1mA Coil Voltage 220VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.1mACoil Voltage220VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time15msRelease Time10msFeaturesSealed - Flux Protection	Manufacturer Part Number	G2R-1-SKVD-AC220
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.1mA Coil Voltage 220VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.1mA Coil Voltage 220VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Category	Relays
Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.1mA Coil Voltage 220VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 4.1mA Coil Voltage 220VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Package	-
Coil Type Non Latching Coil Current 4.1mA Coil Voltage 220VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Series	G2R
Coil Current4.1mACoil Voltage220VACContact FormSPDT (1 Form C)Contact Rating (Current)10ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)176 VACTurn Off Voltage (Min)66 VACOperate Time15msRelease Time10msFeaturesSealed - Flux Protection	Relay Type	General Purpose
Coil Voltage 220VAC Contact Form SPDT (1 Form C) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Coil Current	4.1mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Coil Voltage	220VAC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 176 VAC Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Contact Rating (Current)	10A
Turn Off Voltage (Min) 66 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time10msFeaturesSealed - Flux Protection	Turn On Voltage (Max)	176 VAC
Release Time 10ms Features Sealed - Flux Protection	Turn Off Voltage (Min)	66 VAC
Features Sealed - Flux Protection	Operate Time	15ms
	Release Time	10ms
	Features	Sealed - Flux Protection
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G2R-1-SKVD-AC220 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1-SKVD-AC220 Payment Methods



















G2R-1-SKVD-AC220 Shipping Methods













If you have any question about G2R-1-SKVD-AC220, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com