

G2R-14-H-T130 DC12

G2R-14-H-T130 DC12 Information



G2R-14-H-T130 DC12	
Omron Electronics Inc-EMC Div	
Relays Power Relays, Over 2 Amps	
RELAY GEN PURPOSE SPDT 5A 12V	
-	
For the pricing/inventory/lead time, please contact	
us	
Website: https://www.heisener.com	
E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2R-14-H-T130 DC12 Specifications

Manufacturer Part NumberG2R-14-H-T130 DC12ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mAContact FormSPDT (1 Form C)Contact Rating (Current)SASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)1.8 VDCTurn Off Voltage (Min)1.8 VDCQuerta TimeSmsRelease TimeSmsFeaturesSeled - FullyMounting TypeThrough HoleTermination StyleCip Pin		
CategoryRelaysPackage-Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Otage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)SASwitching Yoltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Of Voltage (Max)1.8 VDCOperate Time5msRelease TimeSmallFeaturesSeld - FullyMounting TypeThrough Hole	Manufacturer Part Number	G2R-14-H-T130 DC12
Power Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12 VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125 VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)SASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease TimeSmsFeaturesSaled - FullyMounting TypeThrough Hole	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease TimeSmaleFeaturesScaled - FullyMounting TypeThrough Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Package	-
Coil TypeNon LatchingCoil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Series	G2R
Coil Current30mACoil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Relay Type	General Purpose
Coil Voltage12VDCContact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease TimeSmallFeaturesSealed - FullyMounting TypeThrough Hole	Coil Type	Non Latching
Contact FormSPDT (1 Form C)Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Coil Current	30mA
Contact Rating (Current)5ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Times5msFeaturesSealed - FullyMounting TypeThrough Hole	Coil Voltage	12VDC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Contact Rating (Current)	5A
Turn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Turn On Voltage (Max)	8.4 VDC
Release Time5msFeaturesSealed - FullyMounting TypeThrough Hole	Turn Off Voltage (Min)	1.8 VDC
FeaturesSealed - FullyMounting TypeThrough Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	5ms
	Features	Sealed - Fully
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

G2R-14-H-T130 DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-14-H-T130 DC12 Payment Methods





If you have any question about G2R-14-H-T130 DC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com