



G2R-14-T130 DC24 Information



For Reference Only

Part Number G2R-14-T130 DC24

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPDT 8A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-14-T130 DC24 Specifications

Manufacturer Part Number G2R-14-T130 DC24 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC Operate Time 15ms		
Category Relays Power Relays, Over 2 Amps Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Manufacturer Part Number	G2R-14-T130 DC24
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Manufacturer	Omron Electronics Inc-EMC Div
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Category	Relays
Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC		Power Relays, Over 2 Amps
Relay Type Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) 3.6 VDC	Package	-
Coil Type Non Latching Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Series	G2R
Coil Current 21.8mA Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Coil Type	Non Latching
Contact Form SPDT (1 Form C) Contact Rating (Current) 8A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Coil Current	21.8mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Coil Voltage	24VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max) 16.8 VDC Turn Off Voltage (Min) 3.6 VDC	Contact Rating (Current)	8A
Turn Off Voltage (Min) 3.6 VDC	Switching Voltage	380VAC, 125VDC - Max
	Turn On Voltage (Max)	16.8 VDC
Operate Time 15ms	Turn Off Voltage (Min)	3.6 VDC
Operate Time 15ms	Operate Time	15ms
Release Time 5ms	Release Time	5ms
Features Sealed - Fully	Features	Sealed - Fully
Mounting Type Through Hole	Mounting Type	Through Hole
Termination Style PC Pin	Termination Style	PC Pin
Report errors?		Report errors?

G2R-14-T130 DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-14-T130 DC24 Payment Methods



















G2R-14-T130 DC24 Shipping Methods













If you have any question about G2R-14-T130 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com