

G2R-1A-AC110 Information



For Reference Only

Part Number G2R-1A-AC110

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 10A 110V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-1A-AC110 Specifications

Manufacturer G2R-1A-AC110 Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		
CategoryRelaysPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.6mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-1A-AC110
Package - G2R Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 10ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Trimination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current10.6mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 10.6mA Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current10.6mACoil Voltage110VACContact FormSPST-NO (1 Form A)Contact Rating (Current)10ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)88 VACTurn Off Voltage (Min)33 VACOperate Time15msRelease Time10msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 110VAC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 10A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Current	10.6mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 88 VAC Turn Off Voltage (Min) 33 VAC Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	110VAC
Switching Voltage Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 380VAC, 125VDC - Max 88 VAC 15ms 15ms 10ms Features PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style 88 VAC 10ms 15ms 10ms PC Pin	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	88 VAC
Release Time 10ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	33 VAC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	10ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Domont owners?	Termination Style	PC Pin
Report errors?		Report errors?

G2R-1A-AC110 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1A-AC110 Payment Methods





















G2R-1A-AC110 Shipping Methods













If you have any question about G2R-1A-AC110, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com