



G2R-1A-E-ASI DC20 Information



For Reference Only

Part Number G2R-1A-E-ASI DC20

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE SPST 16A 20V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









G2R-1A-E-ASI DC20 Specifications

Manufacturer Part Number Manufacturer Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps Package		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current26.5mACoil Voltage20VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)3 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-1A-E-ASI DC20
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 26.5mA Coil Voltage 20VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5 5ms Features Sealed - Flux Protection Mounting Type Trrmination Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current26.5mACoil Voltage20VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)3 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current26.5mACoil Voltage20VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)3 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 26.5mA Coil Voltage 20VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current26.5mACoil Voltage20VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)14 VDCTurn Off Voltage (Min)3 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current Coil Voltage 20VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 20VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Current	26.5mA
Contact Rating (Current) Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style	Coil Voltage	20VDC
Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max) 14 VDC Turn Off Voltage (Min) 3 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min) Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	14 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	3 VDC
Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Flux Protection
•	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
Time		Report errors?

G2R-1A-E-ASI DC20 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1A-E-ASI DC20 Payment Methods



















G2R-1A-E-ASI DC20 Shipping Methods













If you have any question about G2R-1A-E-ASI DC20, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com