

G2R-1A-E DC110

G2R-1A-E DC110 Information

	Power Relays, Over 2 Amps ntion RELAY GEN PURPOSE SPST 16A 110	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2R-1A-E DC110 Specifications

Manufacturer Omron Electronics Inc-EMC Div Category Relays Power Relays, Over 2 Amps Power Relays, Over 2 Amps Package - Stries G2R Relay Type General Purpose Coil Type Non Latching Coil Current 4.8mA Coil Voltage 110VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 77 VDC Turn Off Voltage (Min) 16.5 VDC Operate Time 5ms Release Time Sms Features Sealed - Flux Protection		
CategoryRelaysPackage-Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.8mACoil Voltage110 VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Man)16.5 VDCQuera Time5msRelase Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination Style9C Pin	Manufacturer Part Number	G2R-1A-E DC110
Power Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.8mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time15msRelease TimeSealed - Flux ProtectionFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.8mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time5msRelease TimeSmsFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.8mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time5msRelease TimeSmallFeaturesSealed - Flux ProtectionMounting TypePC Pin		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current4.8mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time5msRelease TimeSealed - Flux ProtectionFeaturesSealed - Flux ProtectionMounting TypePC Pin	Package	-
Coil TypeNon LatchingCoil Current4.8mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time5msRelease Time5msFeaturesScaled - Flux ProtectionMounting TypeThrough HolePer PinPC Pin	Series	G2R
Coil Current4.8mACoil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HolePC PinPC Pin	Relay Type	General Purpose
Coil Voltage110VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time15msRelease TimesSmale - Flux ProtectionMounting TypeThrough HolePermination StylePC Pin	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HolePC Pin	Coil Current	4.8mA
Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HolePremination StylePC Pin	Coil Voltage	110VDC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)77 VDCTurn Off Voltage (Min)16.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleFermination StylePC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min)16.5 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn On Voltage (Max)	77 VDC
Release Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Turn Off Voltage (Min)	16.5 VDC
FeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Operate Time	15ms
Mounting TypeThrough HoleTermination StylePC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Flux Protection
	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

G2R-1A-E DC110 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1A-E DC110 Payment Methods



G2R-1A-E DC110 Shipping Methods



If you have any question about G2R-1A-E DC110, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com