

G2R-1A-E-Y90DC12

G2R-1A-E-Y90DC12 Information

www.helsener	 G2R-1A-E-Y90DC12 Omron Electronics Inc-EMC Div Relays Power Relays, Over 2 Amps RELAY GEN PURPOSE SPST 16A 12V - For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



G2R-1A-E-Y90DC12 Specifications

Manufacturer Part NumberG2R-1A-E-Y90DC12ManufacturerOmron Electronics Inc-EMC DivCategoryRelaysPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mAContact FormSPST-NO (I Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxSwitching Voltage (Max)1.8 VDCTurn On Voltage (Max)1.8 VDCOperate TimeSinsRelase TimeSeal of Flux ProtectionFeaturesSeal of Flux ProtectionMounting TypeContar Flux Protection		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mACoil VoltageI2VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate TimeSinsRelease TimeSealed - Flux ProtectionMounting TypeTurough Hole	Manufacturer Part Number	G2R-1A-E-Y90DC12
PackagePower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate TimeSmsRelease TimeSeided - Flux ProtectionMounting TypeThrough Hole	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate TimeSmsRelease TimeSmsFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease Time5msFeaturesSeld - Flux ProtectionMounting TypeTurogh Hole		Power Relays, Over 2 Amps
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Package	-
Coil TypeNon LatchingCoil Current43.6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Series	G2R
Coil Current43.6mACoil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Relay Type	General Purpose
Coil Voltage12VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time5msRelease TimeSealed - Flux ProtectionFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Coil Type	Non Latching
Contact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Coil Current	43.6mA
Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Coil Voltage	12VDC
Switching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)8.4 VDCTurn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Contact Rating (Current)	16A
Turn Off Voltage (Min)1.8 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Switching Voltage	380VAC, 125VDC - Max
Operate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Turn On Voltage (Max)	8.4 VDC
Release Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough Hole	Turn Off Voltage (Min)	1.8 VDC
Features Sealed - Flux Protection Mounting Type Through Hole	Operate Time	15ms
Mounting Type Through Hole	Release Time	5ms
	Features	Sealed - Flux Protection
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report erro		Report errors?

G2R-1A-E-Y90DC12 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

G2R-1A-E-Y90DC12 Payment Methods



G2R-1A-E-Y90DC12 Shipping Methods



If you have any question about G2R-1A-E-Y90DC12, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com