

### **G2R-1A-EDC60 Information**



For Reference Only

Part Number G2R-1A-EDC60

Manufacturer Omron Electronics Inc-EMC Div

Category Relays

Power Relays, Over 2 Amps

**Description** RELAY GEN PURPOSE SPST 16A 60V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **G2R-1A-EDC60 Specifications**

Manufacturer Part Number     G2R-1A-EDC60       Manufacturer     Omron Electronics Inc-EMC Div       Category     Relays       Power Relays, Over 2 Amps       Package     -       Series     G2R       Relay Type     General Purpose       Coil Type     Non Latching       Coil Current     8.8mA       Coil Voltage     60VDC       Contact Form     SPST-NO (1 Form A)       Contact Rating (Current)     16A       Switching Voltage     380VAC, 125VDC - Max       Turn On Voltage (Max)     42 VDC       Turn Off Voltage (Min)     9 VDC       Operate Time     15ms       Release Time     5ms       Features     Sealed - Flux Protection       Mounting Type     Through Hole       Termination Style     PC Pin		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage60VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)42 VDCTurn Off Voltage (Min)9 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Manufacturer Part Number	G2R-1A-EDC60
Package - Series G2R Relay Type General Purpose Coil Type Non Latching Coil Current 8.8mA Coil Voltage 60VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 42 VDC Turn Off Voltage (Min) 9 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Trinoul SPST-NO (1 Form A) Tronon Style PC Pin	Manufacturer	Omron Electronics Inc-EMC Div
Package-SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage60VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)42 VDCTurn Off Voltage (Min)9 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Category	Relays
SeriesG2RRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current8.8mACoil Voltage60VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)42 VDCTurn Off Voltage (Min)9 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin		Power Relays, Over 2 Amps
Relay Type General Purpose  Coil Type Non Latching  Coil Current 8.8mA  Coil Voltage 60VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 42 VDC  Turn Off Voltage (Min) 9 VDC  Operate Time 15ms  Release Time 5ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Package	-
Coil TypeNon LatchingCoil Current8.8mACoil Voltage60VDCContact FormSPST-NO (1 Form A)Contact Rating (Current)16ASwitching Voltage380VAC, 125VDC - MaxTurn On Voltage (Max)42 VDCTurn Off Voltage (Min)9 VDCOperate Time15msRelease Time5msFeaturesSealed - Flux ProtectionMounting TypeThrough HoleTermination StylePC Pin	Series	G2R
Coil Current Coil Voltage 60VDC Contact Form SPST-NO (1 Form A) Contact Rating (Current) 16A Switching Voltage 380VAC, 125VDC - Max Turn On Voltage (Max) 42 VDC Turn Off Voltage (Min) 9 VDC Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Relay Type	General Purpose
Coil Voltage 60VDC  Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 42 VDC  Turn Off Voltage (Min) 9 VDC  Operate Time 15ms  Release Time 5ms  Release Time 5ms  Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Type	Non Latching
Contact Form SPST-NO (1 Form A)  Contact Rating (Current) 16A  Switching Voltage 380VAC, 125VDC - Max  Turn On Voltage (Max) 42 VDC  Turn Off Voltage (Min) 9 VDC  Operate Time 15ms  Release Time 5ms  Release Time Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Coil Current	8.8mA
Contact Rating (Current)  Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  42 VDC  Turn Off Voltage (Min)  9 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style	Coil Voltage	60VDC
Switching Voltage  380VAC, 125VDC - Max  Turn On Voltage (Max)  42 VDC  Turn Off Voltage (Min)  9 VDC  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Contact Form	SPST-NO (1 Form A)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  42 VDC  9 VDC  15ms  15ms  Features  PC Pin	Contact Rating (Current)	16A
Turn Off Voltage (Min)  Operate Time  15ms  Release Time  5ms  Features  Sealed - Flux Protection  Mounting Type  Through Hole  Termination Style  PC Pin	Switching Voltage	380VAC, 125VDC - Max
Operate Time 15ms Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn On Voltage (Max)	42 VDC
Release Time 5ms Features Sealed - Flux Protection Mounting Type Through Hole Termination Style PC Pin	Turn Off Voltage (Min)	9 VDC
Features Sealed - Flux Protection  Mounting Type Through Hole  Termination Style PC Pin	Operate Time	15ms
Mounting Type Through Hole Termination Style PC Pin	Release Time	5ms
Termination Style PC Pin	Features	Sealed - Flux Protection
·	Mounting Type	Through Hole
Report errors?	Termination Style	PC Pin
		Report errors?

#### **G2R-1A-EDC60** Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **G2R-1A-EDC60 Payment Methods**



















## **G2R-1A-EDC60 Shipping Methods**













If you have any question about G2R-1A-EDC60, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com